

WS-C2960C-12PC-L Datasheet

[Get a Quote](#)

Overview

Cisco Catalyst 2960 Compact 12 ports LAN Base switch supports 12 x 10/100 Fast Ethernet ports with POE which offers 124W available POE power. Cisco 2960 Compact switches are ideal for connecting multiple devices on the retail sales floor and in classrooms, hotels, and factories and for extending wireless LAN networks: wherever space is at a premium and multiple cable runs could be challenging.

Quick Specs

Figure 1 shows the appearance of WS-C2960C-12PC-L.



Table 1 shows the Quick Specs.

Product Code	WS-C2960C-12PC-L
Feature Set	LAN Base
Uplink Interfaces	2 x 1G copper or 2 x 1G SFP
Ports	12 x 10/100 Fast Ethernet
Available POE Power	124W
Forwarding Bandwidth	10 Gbps
RAM	128 MB
Flash Memory	64 MB
Dimensions	4.6 x 26.9 x 23.9 cm
Package Weight	4.38 Kg

Compare to similar item

Table 3 shows the comparison between WS-C2960C-12PC-L and WS-C2960C-8PC-L.

Models	WS-C2960C-12PC-L	WS-C2960C-8PC-L
Uplinks	2 x 1G copper or 2 x 1G SFP	2 x 1G copper or 2 x 1G SFP
Ports	12 x 10/100 Fast Ethernet POE Ports	8 x 10/100 Fast Ethernet POE Ports
Available POE Power	124W	124W
Feature set	LAN Base	LAN Base

Specification

WS-C2960C-12PC-L Specification	
Manufacturer:	Cisco
Product ID:	WS-C2960C-12PC-L
Product Description:	2960C PoE Switch 12 FE PoE, 2 x Dual Purpose Uplink, LAN Base
Product Type:	Ethernet Switch
Marketing Information	
The Cisco Catalyst 3560-C and 2960-C Series compact switches are small form-factor Gigabit Ethernet and Fast Ethernet switches designed for deployments outside the wiring closet. Enterprise and commercial customers can deliver advanced security services, unified communications, wireless, IP video cameras, and other applications for the office workspace, branch office, classroom, cruise ship, and other wiring-constrained environments.	
Interfaces/Ports	
Total Number of Network Ports:	12
Token Ring Port:	No
LRE Port:	No
Uplink Port:	Yes
USB:	Yes

Number of PoE (RJ-45) Ports:	12
Media & Performance	
Ethernet Technology:	Gigabit Ethernet Fast Ethernet
Network Technology:	10/100/1000Base-T 10/100Base-TX
I/O Expansions	
Number of Total Expansion Slots:	2
Expansion Slot Type:	SFP
Shared SFP Slot:	Yes
Number of SFP Slots:	2
Network & Communication	
Layer Supported:	2
Management & Protocols	
Manageable:	Yes
Management:	DHCP QoS VLAN RMON 1,2,3,9 CiscoWorks LMS SNMP v1,v2c,v3 MIB Syslog Web-based Management CLI Telnet
Memory	
Standard Memory:	128 MB
Memory Technology:	DRAM
Flash Memory:	64 MB
Power Description	
PoE (RJ-45) Port:	Yes
Input Voltage:	110 V AC 220 V AC
Power Source:	Power Supply
Physical Characteristics	
Form Factor:	Rack-mountable Desktop Wall Mountable
Height:	1.8" (4.6 cm)
Width:	10.6" (26.9 cm)
Depth:	9.4" (23.9 cm)
Weight (Approximate):	4.10 lb (1.86 Kg)
Package Weight:	9.66 lb (4.38 Kg)

Why: www.linknewnet.com

As a leadouter-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei.H3C](#), [A10](#), [Juniper](#), [Fortinet.F5](#)

Contact Us

- Tel: Address: 3/F,Building B, 312 Jihua Road, Debaoli IndustrialZone, Bantian, Shenzhen, Longgang District, China
- Fax: +86 18038172140
- Email:cs@linknewnet.com