

Overview

The Cisco Firepower 2100 Series is a family of four threat-focused NGFW security platforms that deliver business resiliency through superior threat defense. It offers exceptional sustained performance when advanced threat functions are enabled. These platforms uniquely incorporate an innovative dual multicore CPU architecture that optimizes firewall, cryptographic, and threat inspection functions simultaneously. The series' firewall throughput range addresses use cases from the Internet edge to the data center. Network Equipment Building Standards (NEBS)- compliance is supported by the Cisco Firepower 2100 Series platform. The FPR2130-NGFW-K9 stands for Cisco Firepower 2130 NGFW Appliance, 1RU, 1 x Network Module Bays.

Quick Spec

Figure 1 shows the appearance of FPR2130-NGFW-K9.




Table 1 shows the quick spec.

Product Number	FPR2130-NGFW-K9
Product Description	Cisco Firepower 2130 NGFW Appliance, 1RU, 1 x Network Module Bays
Dimensions (H x W x D)	1.73 x 16.90 x 19.76 in. (4.4 x 42.9 x 50.2 cm)
Form factor (rack units)	1RU
I/O module slots	1 NM slot

Integrated I/O	12 x 10M/100M/1GBASE-T Ethernet interfaces (RJ-45), 4 x 10 Gigabit (SFP+) Ethernet interfaces
Network modules	(FPR-NM-8X10G) 8 x 10 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+) network module
Maximum number of interfaces	Up to 24 total Ethernet ports (12x1G RJ-45, 4x10G SFP+, and network module with 8x10G SFP+)
Integrated network management ports	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)
Serial port	1 x RJ-45 console
USB	1 x USB 2.0 Type-A (500mA)
Storage	1x 200 GB, 1x spare slot (for MSP)

Compare to Similar Items

Table 2 shows the comparison between FPR2130-NGFW-K9 and FPR2120-NGFW-K9.

Product Number	FPR2130-NGFW-K9	FPR2120-NGFW-K9
Product Description	Cisco Firepower 2130 NGFW Appliance, 1RU, 1 x Network Module Bays	Cisco Firepower 2120 NGFW Appliance, 1RU
Dimensions (H x W x D)	1.73 x 16.90 x 19.76 in. (4.4 x 42.9 x 50.2 cm)	1.73 x 16.90 x 19.76 in. (4.4 x 42.9 x 50.2 cm)
Form factor (rack units)	1RU	1RU
I/O module slots	1 NM slot	0
Integrated I/O	12 x 10M/100M/1GBASE-T Ethernet interfaces (RJ-45), 4 x 10 Gigabit (SFP+) Ethernet interfaces	12 x 10M/100M/1GBASE-T Ethernet interfaces (RJ-45), 4 x 1 Gigabit (SFP) Ethernet interfaces
Network modules	(FPR-NM-8X10G) 8 x 10 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+) network module	None
Maximum number of interfaces	Up to 24 total Ethernet ports (12x1G RJ-45, 4x10G SFP+, and network module with 8x10G SFP+)	Up to 16 total Ethernet ports (12x1G RJ-45, 4x1G SFP)
Storage	1x 200 GB, 1x spare slot (for MSP)	1x 100 GB, 1x spare slot (for MSP)

Specification

FPR2130-NGFW-K9 Specification	
Product Number	FPR2130-NGFW-K9
Product Description	Cisco Firepower 2130 NGFW Appliance, 1RU, 1 x Network Module Bays
Hardware Specifications	
Dimensions (H x W x D)	1.73 x 16.90 x 19.76 in. (4.4 x 42.9 x 50.2 cm)
Form factor (rack units)	1RU
I/O module slots	1 NM slot
Integrated I/O	12 x 10M/100M/1GBASE-T Ethernet interfaces (RJ-45), 4 x 10 Gigabit (SFP+) Ethernet interfaces
Network modules	(FPR-NM-8X10G) 8 x 10 Gigabit Ethernet Enhanced Small Form-Factor Pluggable (SFP+) network module
Maximum number of interfaces	Up to 24 total Ethernet ports (12x1G RJ-45, 4x10G SFP+, and network module with 8x10G SFP+)
Integrated network management ports	1 x 10M/100M/1GBASE-T Ethernet port (RJ-45)

Serial port	1 x RJ-45 console
-------------	-------------------

USB	1 x USB 2.0 Type-A (500mA)	
Storage	1x 200 GB, 1x spare slot (for MSP)	
Power supplies	Configuration	Single integrated 250W AC power supply.
	AC input voltage	100 to 240V AC
	AC maximum input current	< 6A at 100V
	AC maximum output power	400W
	AC frequency	50 to 60 Hz
	AC efficiency	>89% at 50% load
	DC input voltage	-48V to -60VDC
	DC maximum input current	< 12.5A at -48V
	DC maximum output power	350W
	DC efficiency	>88% at 50% load
	Redundancy	1+1 AC or DC with dual supplies
Fans	1 hot-swappable fan module (with 4 fans)	
Noise	56 dBA @ 25C 77 dBA at highest system performance.	
Rack mountable	Yes. Mount rails included (4-post EIA-310-D rack)	
Weight	19.4 lb (8.8 kg) 1 x power supplies, 1 x NM, 1 x fan module, 2x SSDs	
Temperature: operating	32 to 104°F (0 to 40°C) or NEBS operation (see below)	
Temperature: nonoperating	-4 to 149°F (-20 to 65°C)	
Humidity: operating	10 to 85% noncondensing	
Humidity: nonoperating	5 to 95% noncondensing	
Altitude: operating	10,000 ft (max) or NEBS operation (see below)	
Altitude: nonoperating	40,000 ft (max)	
NEBS operation	Operating altitude: 0 to 13,000 ft (3962 m) Operating temperature: Long term: 0 to 45°C, up to 6,000 ft (1829 m) Long term: 0 to 35°C, 6,000 to 13,000 ft (1829 to 3964 m) Short term: -5 to 55°C, up to 6,000 ft (1829 m)	

Why: www.linknewnet.com

As a leadouter-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei,H3C](#), [A10](#), [Juniper](#), [Fortinet,F5](#)

Contact Us

- Tel: Address: 3/F,Building B, 312 Jihua Road, Debaoli IndustrialZone, Bantian, Shenzhen, Longgang District, China
- Fax: +86 18038172140
- Email:cs@linknewnet.com