

FPR3140-NGFW-K9

1RU Secure Firewall 3140 (flagship 3100); 8x 1G RJ45 + 8x 1/10/25G SFP+ + 1 NM bay; 45 Gbps FW+AVC, 22.4 Gbps IPsec, 10M concurrent sessions.

Cisco Secure Firewall 3140 Appliance - Threat Defense (Flagship 3100)

The Cisco Secure Firewall 3105 is the entry-level model of the Secure Firewall 3100 Series, providing up to 10 Gbps of firewall + AVC throughput and up to 10 Gbps of NGIPS throughput. It ships with 8 fixed 10/100/1000 RJ-45 ports plus 8 fixed 1/10G SFP+ ports, plus a single network module (NM) bay for additional 1/10G modules. The platform runs Cisco Secure Firewall Threat Defense (FTD) or ASA software and is managed via Firewall Management Center (FMC), Cisco Defense Orchestrator (CDO), or on-device management. The 3105 does not support clustering.

Specification	Value
Series / role	Cisco Secure Firewall 3140 (flagship 3100)
Firewall throughput (FW+AVC, 1024B)	45 Gbps
NGIPS throughput	45 Gbps
IPsec VPN (1024B TCP Fastpath)	22.4 Gbps (projected 39.4 Gbps with VPN Offload)
New connections / sec (FTD)	300,000
Concurrent sessions	10 million (with AVC)
Max VPN peers	20,000
TLS throughput	11.5 Gbps
DRAM / SSD	256 GB / 1x 900 GB NVMe
Power supply	2x 400W AC (1+1 redundant) by default
Clustering	Up to 8 units

- Entry-level 1RU Secure Firewall with 10 Gbps FW+AVC throughput.
- 8 fixed 1G RJ-45 + 8 fixed 1/10G SFP+ ports plus a single NM bay for 1/10G modules.
- Runs Cisco FTD (Snort 3) or ASA software - managed via FMC, CDO, or on-device.
- Up to 1.5 million concurrent sessions and 90,000 new connections/sec.
- Single 400W AC PSU ships by default; second PSU optional for redundancy.

Specification	FPR3140-NGFW-K9
Firewall (FW+AVC, 1024B)	45 Gbps
NGIPS / IPS (FW+AVC+IPS, 1024B)	45 Gbps

Specification	FPR3140-NGFW-K9
IPsec VPN (1024B TCP Fastpath)	22.4 Gbps (projected 39.4 Gbps with VPN Offload)
New connections / sec (FTD)	300,000
Concurrent sessions (with AVC)	10 million
Max VPN peers	20,000
TLS throughput	11.5 Gbps
Clustering	Up to 8 units

The platform runs Cisco Secure Firewall Threat Defense (FTD) image by default with Snort 3 detection engine. The capabilities below are supported through the FTD software.

Capability	Description
Stateful firewall	Layer 3/4 stateful inspection with zones, interfaces, and ACLs
NGFW / Application visibility	Application Visibility and Control (AVC) with NBAR2/L7 inspection
Intrusion prevention (IPS)	Cisco Talos-backed signatures; Snort 3 with custom rule sets
URL filtering	Categorical and reputation-based URL filtering (Cisco Talos cloud)
Advanced Malware Protection	Cisco AMP / AMP Threat Grid sandbox integration
TLS / SSL inspection	Inline decryption for threat inspection (where licensed)
Cisco Umbrella integration	DNS-layer security via Cisco Umbrella SIG (where licensed)
DNS layer security	DNS-layer policy and threat enforcement
VPN (site-to-site, RA)	IPsec / IKEv2 / DTLS; hub-spoke and remote-access VPN
High availability	Active/active and active/standby failover pairs (where supported)
Clustering	Multi-chassis clustering for carrier-class scale (where supported)
Management planes	FMC (central), CDO (cloud), local management (platform capable)

The platform runs Cisco Secure Firewall Threat Defense (FTD) software. Key software capabilities and their operational role are summarized below.

Feature	Role
Snort 3 engine	Multi-threaded next-gen IPS with Talos signature feed
Application Visibility (AVC)	L7 application recognition and policy enforcement
URL filtering	Category / reputation based URL control
Advanced Malware Protection (AMP)	File / malware inspection and threat grid sandboxing
TLS / SSL inspection	Inline decryption for encrypted-threat visibility
Stateful firewall	Zone-based stateful inspection and NAT

Feature	Role
DNS security (Umbrella)	DNS-layer policy via Cisco Umbrella integration
Multi-instance (VDC)	Virtual firewall instances on one chassis (where supported)
Management	FMC central, CDO cloud, REST API / NETCONF-YANG
Reporting	FMC dashboards, syslog / CEF to SIEM
Auto-update	Talos signature and rule auto-update
Policy automation	REST API and templates for orchestration

Cisco Secure Firewall (FTD) platforms support several deployment modes to fit the network topology. The mode is chosen at initial configuration and managed centrally via FMC or CDO.

Mode / Configuration	Description
Routed firewall	Layer-3 routed interfaces with zones and inter-zone policies
Transparent (bump-in-the-wire)	Layer-2 bridge groups for inline insertion without renumbering
Inline IPS / IDS	Inline pair or passive IDS using the IPS interfaces (Snort 3)
Multi-instance	Virtual firewalls on one appliance (FTD multi-instance, where supported)
High availability	Active/standby or active/active stateful failover pairs
Clustering	Multi-chassis clustering up to 16 chassis (where supported)
Zero-touch deployment	PnP / ZTP enrollment via Cisco Defense Orchestrator
VPN	Site-to-site, remote-access (RA) VPN, hub-spoke topologies
Interface redundancy	Redundant / EtherChannel interface groups
Fail-to-wire	Inline security modules with fail-open bypass (where supported)
AVC / NBAR	Application-aware policies and per-application visibility
TLS decryption	Inline SSL/TLS inspection policies (where licensed)

Cisco Secure Firewall platforms support a rich set of operational and high-availability features to keep threat defense active and policy-driven in production deployments.

Capability	Description
Active/standby failover	Stateful failover with configuration and session sync
Active/active failover	Active/active failover for data center deployments (where supported)
Multi-chassis clustering	Up to 16 chassis cluster for carrier-class scale (where supported)
Zero-touch provisioning	PnP and ZTP through the Cisco Defense Orchestrator
Smart licensing	Cisco Smart Licensing with PnP enrollment and offline reservation
REST API	Full REST API for automation and policy orchestration
NETCONF/YANG	NETCONF / YANG models for FTD configuration and telemetry

Capability	Description
Syslog / SIEM	Syslog export and CEF-format delivery to SIEM collectors
Threat intelligence	Cisco Talos automatic signature feed; Snort 3 rule updates
Sandboxing	Cisco AMP Threat Grid sandbox integration
Encrypted traffic analytics	ETA on supported platforms (where licensed)
Backup / restore	FMC-managed configuration and policy backup / restore

The chassis supports a range of fixed and modular network interfaces through the available network-module bays for FPR3140-NGFW-K9.

Module / Accessory	Description
Network modules (1G/10G/25G)	NM with 8x1/10/25G SFP+ ports (platform dependent)
Network modules (40G/100G)	NM with 4x40G QSFP+ or 2x100G QSFP28 ports (platform dependent)
Fail-to-wire (FTW) modules	FTW 8x1G copper or 6x10G/25G SR/LR fiber network modules
SFP / SFP+ optics	GLC-T (1G copper), GLC-SX-MMD / -LX-SMD (1G SX/LX); SFP-10G-SR/LR
SFP28 25G optics	SFP-25G-SR-S, SFP-25G-LR-S (where 25G ports available)
QSFP / QSFP28 optics	QSFP-40G-SR4/LR4; QSFP-100G-SR4-S / -LR4-S (where 100G available)
Power supply	AC 400W / 1900W PSU (platform dependent); DC options where available
Spare fan tray	Hot-swappable fan module (FRU) for field replacement
Console / management	RJ-45 console cable included for local management
Rack-mount kit	Standard 19-in four-post EIA-310-D rack-mount brackets included
Cisco Defense Orchestrator	Cloud-based management subscription for centralized policy
FMC license	Firewall Management Center feature license tier (per-platform)

The platform complies with the following interoperability, safety and environmental standards. Compliance is verified by independent testing laboratories.

Category	Standard
IPsec / VPN	RFC 4303 ESP, RFC 7296 IKEv2, RFC 5246 TLS 1.2, RFC 8446 TLS 1.3, AES-GCM
IP routing	RFC 1812 IPv4, RFC 4291 IPv6; OSPFv2/v3, IS-IS, BGP-4, MP-BGP, static
High availability	Active/active and active/standby failover; multi-chassis clustering
Threat intelligence	Cisco Talos signature feeds and sandbox integration
DNS / URL filtering	Cisco Umbrella DNS-layer; URL reputation feed (Talos)
Management	REST API, NETCONF/YANG (FTD), SNMPv2c/v3, FMC/CDO central management
Quality of Service	802.1p, DSCP (RFC 2474), RFC 2597/2598 PHB

Category	Standard
Safety	UL/CSA/IEC/EN 62368-1, IEC 60950-1, AS/NZS 62368-1, GB4943
EMC / EMI	FCC 47 CFR Part 15 Class A, EN 55032/CISPR 32, EN 55024/55035, EN 300 386
Environmental	RoHS 2011/65/EU, WEEE 2012/19/EU; NEBS Level-3 where indicated

The platform runs Cisco Secure Firewall Threat Defense (FTD) image by default with Snort 3 detection engine. The capabilities below are supported through the FTD software.

Capability	Description
Stateful firewall	Layer 3/4 stateful inspection with zones, interfaces, and ACLs
NGFW / Application visibility	Application Visibility and Control (AVC) with NBAR2/L7 inspection
Intrusion prevention (IPS)	Cisco Talos-backed signatures; Snort 3 with custom rule sets
URL filtering	Categorical and reputation-based URL filtering (Cisco Talos cloud)
Advanced Malware Protection	Cisco AMP / AMP Threat Grid sandbox integration
TLS / SSL inspection	Inline decryption for threat inspection (where licensed)
Cisco Umbrella integration	DNS-layer security via Cisco Umbrella SIG (where licensed)
DNS layer security	DNS-layer policy and threat enforcement
VPN (site-to-site, RA)	IPsec / IKEv2 / DTLS; hub-spoke and remote-access VPN
High availability	Active/active and active/standby failover pairs (where supported)
Clustering	Multi-chassis clustering for carrier-class scale (where supported)
Management planes	FMC (central), CDO (cloud), local management (platform capable)

The platform runs Cisco Secure Firewall Threat Defense (FTD) software. Key software capabilities and their operational role are summarized below.

Feature	Role
Snort 3 engine	Multi-threaded next-gen IPS with Talos signature feed
Application Visibility (AVC)	L7 application recognition and policy enforcement
URL filtering	Category / reputation based URL control
Advanced Malware Protection (AMP)	File / malware inspection and threat grid sandboxing
TLS / SSL inspection	Inline decryption for encrypted-threat visibility
Stateful firewall	Zone-based stateful inspection and NAT
DNS security (Umbrella)	DNS-layer policy via Cisco Umbrella integration
Multi-instance (VDC)	Virtual firewall instances on one chassis (where supported)
Management	FMC central, CDO cloud, REST API / NETCONF-YANG

Feature	Role
Reporting	FMC dashboards, syslog / CEF to SIEM
Auto-update	Talos signature and rule auto-update
Policy automation	REST API and templates for orchestration

Cisco Secure Firewall (FTD) platforms support several deployment modes to fit the network topology. The mode is chosen at initial configuration and managed centrally via FMC or CDO.

Mode / Configuration	Description
Routed firewall	Layer-3 routed interfaces with zones and inter-zone policies
Transparent (bump-in-the-wire)	Layer-2 bridge groups for inline insertion without renumbering
Inline IPS / IDS	Inline pair or passive IDS using the IPS interfaces (Snort 3)
Multi-instance	Virtual firewalls on one appliance (FTD multi-instance, where supported)
High availability	Active/standby or active/active stateful failover pairs
Clustering	Multi-chassis clustering up to 16 chassis (where supported)
Zero-touch deployment	PnP / ZTP enrollment via Cisco Defense Orchestrator
VPN	Site-to-site, remote-access (RA) VPN, hub-spoke topologies
Interface redundancy	Redundant / EtherChannel interface groups
Fail-to-wire	Inline security modules with fail-open bypass (where supported)
AVC / NBAR	Application-aware policies and per-application visibility
TLS decryption	Inline SSL/TLS inspection policies (where licensed)

Cisco Secure Firewall platforms support a rich set of operational and high-availability features to keep threat defense active and policy-driven in production deployments.

Capability	Description
Active/standby failover	Stateful failover with configuration and session sync
Active/active failover	Active/active failover for data center deployments (where supported)
Multi-chassis clustering	Up to 16 chassis cluster for carrier-class scale (where supported)
Zero-touch provisioning	PnP and ZTP through the Cisco Defense Orchestrator
Smart licensing	Cisco Smart Licensing with PnP enrollment and offline reservation
REST API	Full REST API for automation and policy orchestration
NETCONF/YANG	NETCONF / YANG models for FTD configuration and telemetry
Syslog / SIEM	Syslog export and CEF-format delivery to SIEM collectors
Threat intelligence	Cisco Talos automatic signature feed; Snort 3 rule updates
Sandboxing	Cisco AMP Threat Grid sandbox integration

Capability	Description
Encrypted traffic analytics	ETA on supported platforms (where licensed)
Backup / restore	FMC-managed configuration and policy backup / restore

The chassis supports a range of fixed and modular network interfaces through the available network-module bays for FPR3140-NGFW-K9.

Module / Accessory	Description
Network modules (1G/10G/25G)	NM with 8x1/10/25G SFP+ ports (platform dependent)
Network modules (40G/100G)	NM with 4x40G QSFP+ or 2x100G QSFP28 ports (platform dependent)
Fail-to-wire (FTW) modules	FTW 8x1G copper or 6x10G/25G SR/LR fiber network modules
SFP / SFP+ optics	GLC-T (1G copper), GLC-SX-MMD / -LX-SMD (1G SX/LX); SFP-10G-SR/LR
SFP28 25G optics	SFP-25G-SR-S, SFP-25G-LR-S (where 25G ports available)
QSFP / QSFP28 optics	QSFP-40G-SR4/LR4; QSFP-100G-SR4-S / -LR4-S (where 100G available)
Power supply	AC 400W / 1900W PSU (platform dependent); DC options where available
Spare fan tray	Hot-swappable fan module (FRU) for field replacement
Console / management	RJ-45 console cable included for local management
Rack-mount kit	Standard 19-in four-post EIA-310-D rack-mount brackets included
Cisco Defense Orchestrator	Cloud-based management subscription for centralized policy
FMC license	Firewall Management Center feature license tier (per-platform)

The platform complies with the following interoperability, safety and environmental standards. Compliance is verified by independent testing laboratories.

Category	Standard
IPsec / VPN	RFC 4303 ESP, RFC 7296 IKEv2, RFC 5246 TLS 1.2, RFC 8446 TLS 1.3, AES-GCM
IP routing	RFC 1812 IPv4, RFC 4291 IPv6; OSPFv2/v3, IS-IS, BGP-4, MP-BGP, static
High availability	Active/active and active/standby failover; multi-chassis clustering
Threat intelligence	Cisco Talos signature feeds and sandbox integration
DNS / URL filtering	Cisco Umbrella DNS-layer; URL reputation feed (Talos)
Management	REST API, NETCONF/YANG (FTD), SNMPv2c/v3, FMC/CDO central management
Quality of Service	802.1p, DSCP (RFC 2474), RFC 2597/2598 PHB
Safety	UL/CSA/IEC/EN 62368-1, IEC 60950-1, AS/NZS 62368-1, GB4943
EMC / EMI	FCC 47 CFR Part 15 Class A, EN 55032/CISPR 32, EN 55024/55035, EN 300 386

Category	Standard
Environmental	RoHS 2011/65/EU, WEEE 2012/19/EU; NEBS Level-3 where indicated