

7606-2SUP7203B-2PS - Cisco 7606 Router

Model: 7606-2SUP7203B-2PS | Brand: CISCO

Product Overview

Cisco 7606 Chassis, 6-slot, 2 SUP7203B, 2 Power Supply

Product page: <https://www.linknewnet.com/products/7606-2sup7203b-2ps>

Quick Specifications

Attribute	Value
Product Type	Used Chassis
Brand	Cisco
Model	7606-2SUP7203B-2PS
Chassis Type	6-slot
Supervisors Included	2 x SUP7203B
Power Supplies Included	2
Interface Slots	6
Dimensions (H x W x D)	17.5" x 17.3" x 21.25"
Maximum Capacity	240 Gbps
Forwarding Rate	30 Mpps
Management	CLI, SNMP, RMON
Redundant Power Supplies	Yes
Layer Supported	Layer 2, Layer 3
Operating Temperature	32°F to 104°F (0°C to 40°C)
Storage Temperature	-40°F to 167°F (-40°C to 75°C)
Relative Humidity	5% to 90% (non-condensing)
Mounting	Rack-mountable
Compliance	FCC, CE, UL
Backplane	1.2 Tbps
Performance	240 Gbps full-duplex
Product Code	7606-2SUP7203B-2PS
Brand	CISCO

Replacement / Alternative Options

If the 7606-2SUP7203B-2PS is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
7606-2SUP720XL-2PS	Cisco 7606 6-slot, Redundant System, 2 SUP720-3BXL and 2 PS
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of 7606-2SUP7203B-2PS or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).