

7606S-S32-10G-B-R - Cisco 7606 Router

Model: 7606S-S32-10G-B-R | Brand: CISCO

Product Overview

Cisco 7606S Chassis,6-slot,Redundant SUP32-2X10GE-3B,PS

Product page: <https://www.linknewnet.com/products/7606s-s32-10g-b-r>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	7606S-S32-10G-B-R (USED)
Chassis Slots	6
Supervisor Engine	SUP32-2X10GE-3B
Redundancy	Yes
Power Supply	Redundant
Rack Units	10U
Form Factor	Rack-Mountable
Network Interfaces	2x 10GE
Switching Capacity	240 Gbps
Forwarding Rate	30 Mpps
Dimensions	17.5 x 17.3 x 24 in
Memory	Up to 2 GB
Operating Temperature	32°F to 104°F (0°C to 40°C)
Storage Temperature	-4°F to 149°F (-20°C to 65°C)
Relative Humidity	10% to 90%, non-condensing
MTBF	80,000 hours
Power Consumption	750W
Airflow	Side-to-Side
Port Density	48 10/100/1000 ports
Product Code	7606S-S32-10G-B-R
Brand	CISCO

Replacement / Alternative Options

If the 7606S-S32-10G-B-R is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
7606S-RSP720C-P	Cisco 7606S Chassis,6-slot,RSP720-3C,PS
7606S-RSP720C-R	Cisco 7606S Chassis,6-slot,Redundant System,2RSP720-3C,2PS

Request availability: [Ask for current stock](#) of 7606S-S32-10G-B-R or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).