

7606S-S32-8G-B-R - Cisco 7606 Router

Model: 7606S-S32-8G-B-R | Brand: CISCO

Product Overview

Cisco 7606S Chassis,6-slot,Redundant SUP32-8GE-3B,PS

Product page: <https://www.linknewnet.com/products/7606s-s32-8g-b-r>

Quick Specifications

Attribute	Value
Product Brand	Cisco
Product Name	7606S-S32-8G-B-R (USED)
Chassis	6-slot
Supervisor Engine	Redundant SUP32-8GE-3B
Power Supply	PS
Max Aggregate Throughput	240 Gbps
Dimensions	20.83 x 17.25 x 12.25 inches
Network Interfaces	8 Gigabit Ethernet ports
Redundancy Support	Yes
MPLS Support	Yes
Layer Support	Layer 2 and Layer 3
Memory	1 GB DRAM
Flash Memory	512 MB
Switch Fabric Capacity	32 Gbps
Routing Protocols	OSPF, EIGRP, BGP
QoS Support	Yes
Regulatory Compliance	CE, FCC
Operating Temperature	32 to 104°F (0 to 40°C)
Storage Temperature	-4 to 149°F (-20 to 65°C)
MTBF	92,000 hours
Product Code	7606S-S32-8G-B-R
Brand	CISCO

Replacement / Alternative Options

If the 7606S-S32-8G-B-R is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
7606S-RSP720C-P	Cisco 7606S Chassis,6-slot,RSP720-3C,PS
7606S-RSP720C-R	Cisco 7606S Chassis,6-slot,Redundant System,2RSP720-3C,2PS

Request availability: [Ask for current stock](#) of 7606S-S32-8G-B-R or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).