

7606S-SUP720B-P - Cisco 7606 Router

Model: 7606S-SUP720B-P | Brand: CISCO

Product Overview

Cisco 7606S Chassis,6-slot,SUP720-3B,PS

Product page: <https://www.linknewnet.com/products/7606s-sup720b-p>

Quick Specifications

Attribute	Value
Brand	Cisco
Product Name	7606S-SUP720B-P
Chassis	6-slot
Supervisor Engine	SUP720-3B
Condition	USED
Power Supply	Included
Rack Units	6U
Forwarding Rate	30 Mpps
Switch Fabric Capacity	720 Gbps
Interfaces	Varies by line card
Redundancy	Yes
Operating Temperature	0°C to 40°C
Storage Temperature	-40°C to 70°C
Humidity Range (Operating)	10% to 90% (non-condensing)
Humidity Range (Storage)	5% to 95% (non-condensing)
Max Power Consumption	1800W
Dimensions (D x W x H)	17.5 in x 17.3 in x 12.3 in
Protocols Supported	BGP, OSPF, EIGRP, ISIS, MPLS
Flash Memory	512 MB
DRAM Memory	1024 MB
Product Code	7606S-SUP720B-P
Brand	CISCO

Replacement / Alternative Options

If the 7606S-SUP720B-P is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
7606S-RSP720C-P	Cisco 7606S Chassis,6-slot,RSP720-3C,PS
7606S-RSP720C-R	Cisco 7606S Chassis,6-slot,Redundant System,2RSP720-3C,2PS

Request availability: [Ask for current stock](#) of 7606S-SUP720B-P or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).