

7609-2SUP720XL-2PS - Cisco 7609 Router

Model: 7609-2SUP720XL-2PS | Brand: CISCO

Product Overview

Cisco 7609 9-slot, Redundant System, 2 SUP720-3BXL and 2 PS

Product page: <https://www.linknewnet.com/products/7609-2sup720xl-2ps>

Quick Specifications

Attribute	Value
Model	Cisco 7609
Form Factor	9-slot chassis
Redundancy	Yes, Redundant System
Supervisors	2 x SUP720-3BXL
Power Supplies	2 x Power Supplies (PS)
Switch Fabric Capacity	720 Gbps
Routing Engine	PFC3BXL
DRAM	1 GB (default), upgradable to 2 GB
Flash Memory	512 MB
Layer Support	Layer 2 and Layer 3
Chassis Dimensions	17.5 x 17.31 x 24.57 inches
Mount Type	Rack-mountable
Ethernet Interface Types	10/100/1000 Ethernet
Operating Temperature	32 to 104°F (0 to 40°C)
Storage Temperature	-40 to 158°F (-40 to 70°C)
Relative Humidity	10% to 90%, non-condensing
Input Voltage	100-240 VAC
Power Consumption	1500 Watts
Maximum Pre-Owned Warranty	90 days
Software	Cisco IOS
Product Code	7609-2SUP720XL-2PS
Brand	CISCO

Replacement / Alternative Options

If the 7609-2SUP720XL-2PS is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
7609-2SUP7203B-2PS	Cisco 7609 Chassis, 9-slot, 2 SUP7203B, 2 Power Supply
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of 7609-2SUP720XL-2PS or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).