

7609S-SUP720B-R - Cisco 7609 Router

Model: 7609S-SUP720B-R | Brand: CISCO

Product Overview

Cisco 7609S Chassis,9-slot,Redundant System,2SUP720-3B,2PS

Product page: <https://www.linknewnet.com/products/7609s-sup720b-r>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	7609S-SUP720B-R (USED)
Chassis Type	7600 Series
Slot Capacity	9 slots
Redundancy	Yes, Redundant System
Supervisor Engines	2 x SUP720-3B
Power Supplies	2 x Power Supply
Routing Protocols	BGP, EIGRP, OSPF, RIP
Switching Capacity	720 Gbps
Forwarding Rate	400 Mpps
Rack Units (RU)	15 RU
Network Management	Cisco IOS Software
Interfaces	10/100/1000 Mbps Ethernet
Maximum Power Consumption	1830 Watts
Cooling	Redundant, Hot-swappable Fans
Dimensions (H x W x D)	26.1" x 17.3" x 18.9"
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Relative Humidity	10% - 90%, non-condensing
Airflow	Front-to-Back
Product Code	7609S-SUP720B-R
Brand	CISCO

Replacement / Alternative Options

If the 7609S-SUP720B-R is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
7609S-RSP720C-P	Cisco 7609S Chassis,9-slot,RSP720-3C,PS
7609S-RSP720C-R	Cisco 7609S Chassis,9-slot,Redundant System,2RSP720-3C,2PS

Request availability: [Ask for current stock](#) of 7609S-SUP720B-R or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).