

8202-SYS - Cisco Routers 8000 Series

Model: 8202-SYS | Brand: CISCO

Product Overview

Cisco 8202 2 RU Chassis with 12x400 GbE QSFP56-DD and 60x100 GbE QSFP28 and 32 GB of DRAM

Product page: <https://www.linknewnet.com/products/8202-sys>

Quick Specifications

Attribute	Value
Operating temperature	32 to 104°F (0 to 40°C)
Nonoperating temperature	-40 to 158°F (-40 to 70°C)
Humidity	5% to 95% (noncondensing)
Altitude	0 to 9842 ft. (0 to 3000 m)
Power Supply	2 power supplies
Typical system power	Typical system power at 10.8 Tbps: 750 W
Dimension	(H) 3.45 x (W) 17.3 x (D) 20.1 in. (8.77 x 43.9 x 51.1 cm) – 2 RU
Regulatory compliance	Products should comply with CE Markings according to directives 2004/108/EC and 2006/95/EC.
Safety	UL 60950-1 Second Edition CAN/CSA-C22.2 No. 60950-1 Second Edition EN 60950-1 Second Edition IEC 60950-1 Second Edition AS/NZS 60950-1 GB4943
RoHS	The product is RoHS-6 compliant with exceptions for leaded-ball grid-array (BGA) balls and lead press-fit connectors.
Product Code	8202-SYS
Brand	CISCO

Replacement / Alternative Options

If the 8202-SYS is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of 8202-SYS or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).