

A9K-200G-IVRF - Cisco ASR 9000 Series Line Card

Model: A9K-200G-IVRF | Brand: CISCO

Product Overview

Infrastructure VRF license to activate up to 8 VRF instances per 200G modular line card

Product page: <https://www.linknewnet.com/products/a9k-200g-ivrf>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	A9K-200G-IVRF
Product Type	Line Card
Capacity	200 Gbps
Supported Standards	802.3 Ethernet, 802.3u Fast Ethernet, 802.3z Gigabit Ethernet
Interface Type	SFP+
Port Count	20 x 10G ports / 2 x 100G ports
Power Requirement	400W
Relative Humidity (Operational)	5% to 95% (Non-condensing)
Relative Humidity (Storage)	5% to 95% (Non-condensing)
MTBF	1,200,000 hours
Software Compatibility	IOS XR
Form Factor	Plug-in module
Dimensions	3.2 x 14.2 x 11.2 inches
Protocols Supported	IPv4, IPv6
Redundancy	Yes, N+1
Cooling	Front to back air flow
Certification	RoHS, CE
Product Code	A9K-200G-IVRF
Brand	CISCO

Replacement / Alternative Options

If the A9K-200G-IVRF is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
A9K-20HG-FLEX-FC=	ASR 9000 2T Flexible Consumption Combo Line Card - 5th Gen
A9K-20HG-FLEX-SE	ASR 9000 2T Service Edge Combo Line Card - 5th Generation

Request availability: [Ask for current stock](#) of A9K-200G-IVRF or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).