

Cisco A9K-2T20GE-B Line Card for ASR 9000 Series RSP

Model: A9K-2T20GE-B | Brand: CISCO

Product Overview

Cisco ASR 9000 Line Card A9K-2T20GE-B 2-Port 10GE, 20-Port GE Line Card, Requires XFPs and SFPs

Product page: <https://www.linknewnet.com/products/a9k-2t20ge-b>

Quick Specifications

Attribute	Value
Part Number	A9K-2T20GE-B
Product Description	2-Port 10GE, 20-Port GE Medium Queue Combo Line Card, requires XFPs for 10GE, SFPs for GE
Total queues	96,000 – 192,000
Policers	64,000 – 128,000
Ethernet flow points (EFPs)	16,000
Connectivity	10-Mbps, 100-Mbps, 1-Gbps, and 10-Gbps 802.3 Ethernet
Memory	4 GB DRAM
Options	Each line card is available as either a low queue, base or extended line card.
Physical dimensions (H x W x D); weight	14 x 1.72 x 20.5 in.(35.56 x 4.37 x 52.07 cm) 14 – 19 lb (6.35 – 8.62 kg)
Power	Maximum 350W – 630W (depending on the card type); typical 310W – 565W (depending on the card type)
Product Code	A9K-2T20GE-B
Brand	CISCO

Replacement / Alternative Options

If the A9K-2T20GE-B is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
A9K-2T20GE-E	Cisco ASR 9000 Line Card A9K-2T20GE-E 2-Port 10GE, 20-Port GE Extended LC, Req. XFPs and SFPs
A9K-2T20GE-L	Cisco ASR 9000 Line Card A9K-2T20GE-L 2-Port 10GE, 20-Port GE Low Queue LC Requires XFPs and SFPs

Request availability: [Ask for current stock](#) of A9K-2T20GE-B or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).