

A9K-ISM-100 - Cisco ASR 9000 Series Service Module

Model: A9K-ISM-100 | Brand: CISCO

Product Overview

Cisco A9K-ISM-100 ASR 9000 Integrated Service 2x CPU 48G DRAM Router Module

Product page: <https://www.linknewnet.com/products/a9k-ism-100>

Quick Specifications

Attribute	Value
Type	Cisco ASR 9000 Module AVSM ISM 40G
Redundancy	· No single point of failure · Fabric redundancy · Power supply redundancy · ISM redundancy (through CDSM)
Power input	· Worldwide ranging AC: 200–240V; 50–60 Hz; 16A nominal · Worldwide ranging DC: –48V to –60V; –54V; 50A nominal
Power consumption	· Typical: 330W · Maximum: 450W
Storage temperature	–40 to 158°F (–40 to 70°C)
Storage (relative humidity)	5 to 95% Note: Not to exceed 0.024 kg water or dry air.
Operating altitude	–60 to 4000m (up to 2000m conforms to IEC/EN/UL/CSA 60950 requirements)
Product Code	A9K-ISM-100
Brand	CISCO

Replacement / Alternative Options

If the A9K-ISM-100 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of A9K-ISM-100 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).