

A9K-SIP-700-2PK - Cisco ASR 9000 Series SPA Interface

Model: A9K-SIP-700-2PK | Brand: CISCO

Product Overview

Cisco ASR 9000 Interface A9K-SIP-700-2PK 2-Pack bundle for ASR-9000 SIP-700 Thor LC w/ Min 2x SPA's

Product page: <https://www.linknewnet.com/products/a9k-sip-700-2pk>

Quick Specifications

Attribute	Value
Type	2-Pack bundle for ASR-9000 SIP-700 Thor LC w/ Min 2x SPA's
Chassis compatibility	All Cisco ASR 9000 Series chassis
Software compatibility	Cisco IOS XR Software Release 3.9 or later
Density	Up to 4 single-height SPAs or Up to 2 double-height SPAs or A combination of the two – subject to above restrictions
Physical dimensions (H x W x D); weight	14 x 1.72 x 20.5 in.; 14 lb
Power	375W (maximum)
Operating temperature (nominal)	41 to 104°F (5 to 40°C)
Operating temperature (short-term)	23 to 131°F (–5 to 55°C)
Storage temperature	–40 to 158°F (–40 to 70°C)
Storage (relative humidity)	5 to 95% Note: Not to exceed 0.024 kg water per kg of dry air
Operating altitude	–60 to 4000m (up to 2000m conforms to IEC, EN, UL, and CSA 60950 requirements)
Product Code	A9K-SIP-700-2PK
Brand	CISCO

Replacement / Alternative Options

If the A9K-SIP-700-2PK is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
A9K-SIP-700	Cisco ASR 9000 Interface A9K-SIP-700 Cisco ASR 9000 Series SPA Interface Processor-700
A9K-SIP-700	Cisco ASR 9000 Series Interface Module A9K-SIP-700 SPA Interface Processor-700

Request availability: [Ask for current stock](#) of A9K-SIP-700-2PK or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).