

Cisco Aironet 1852E Access Point - AIR-AP1852E-T-K9

Model: AIR-AP1852E-T-K9 | Brand: CISCO

Product Overview

802.11ac Wave 2 Access Point, 4x4:4, External-Ant, T Regulatory Domain

Product page: <https://www.linknewnet.com/products/air-ap1852e-t-k9>

Quick Specifications

Attribute	Value
Description	802.11ac Wave 2 Access Point, 4x4:4, External-Ant, T Regulatory Domain
Software	Cisco Unified Wireless Network Software Release with AireOS wireless controllers: 8.1 MR1 or later for the Cisco Aironet 1850 Series Access Points
Deployment modes	Centralized local, Standalone, Sniffer, Cisco FlexConnect, Monitor, OfficeExtend, Mesh
Indicators	Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors
Dimensions (W x L x H)	Access point (without mounting bracket): 8.3 x 8.3 x 2 in. (210.8 x 210.8 x 50.8 mm)
Weight	3.12 lb (1.41 kg)
System memory	1 GB DRAM 256 MB Flash
Input power requirements	AP1850: 44 to 57 VDC Power supply and power injector: 100 to 240 VAC; 50 to 60 Hz
Warranty	Limited lifetime hardware warranty
Product Code	AIR-AP1852E-T-K9
Brand	CISCO

Replacement / Alternative Options

If the AIR-AP1852E-T-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
AIR-AP-BRACKET-9=	C9130AXE antenna bracket
AIR-AP1041N-A-K9	Cisco 1040 Access Point AIR-AP1041N-A-K9 802.11g/n Fixed Auto AP; Int Ant; A Reg Domain

Request availability: [Ask for current stock](#) of AIR-AP1852E-T-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).