

Cisco Aironet 1852i Access Point - AIR-AP1852I-T-K9

Model: AIR-AP1852I-T-K9 | Brand: CISCO

Product Overview

802.11ac Wave 2 Access Point, 4x4:4, Internal Antenna, T Regulatory Domain

Product page: <https://www.linknewnet.com/products/air-ap1852i-t-k9>

Quick Specifications

Attribute	Value
Description	802.11ac Wave 2 Access Point, 4x4:4, Internal-Ant, T Regulatory Domain
Software	Cisco Unified Wireless Network Software Release with AireOS wireless controllers: 8.1 MR1 or later for the Cisco Aironet 1850 Series Access Points
Deployment modes	Centralized local, Standalone, Sniffer, Cisco FlexConnect, Monitor, OfficeExtend, Mesh
Integrated antenna	2.4 GHz, gain 3 dBi, internal omni, horizontal beamwidth 360° 5 GHz, gain 5 dBi, internal omni, horizontal beamwidth 360°
Indicators	Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors
Dimensions (W x L x H)	Access point (without mounting bracket): 8.3 x 8.3 x 2 in. (210.8 x 210.8 x 50.8 mm)
Weight	3.12 lb (1.41 kg)
System memory	1 GB DRAM 256 MB flash
Input power requirements	AP1850: 44 to 57 VDC Power supply and power injector: 100 to 240 VAC; 50 to 60 Hz
Warranty	Limited lifetime hardware warranty
Product Code	AIR-AP1852I-T-K9
Brand	CISCO

Replacement / Alternative Options

If the AIR-AP1852I-T-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
AIR-AP-BRACKET-9=	C9130AXE antenna bracket
AIR-AP1041N-A-K9	Cisco 1040 Access Point AIR-AP1041N-A-K9 802.11g/n Fixed Auto AP; Int Ant; A Reg Domain

Request availability: [Ask for current stock](#) of AIR-AP1852I-T-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).