

AIR-AP3802I-S-K9 - Cisco Aironet 3802i Access Point

Model: AIR-AP3802I-S-K9 | Brand: CISCO

Product Overview

802.11ac Wave 2 AP w/CleanAir, 4x4:3, Mod, Internal Antenna, mGig, S Regulatory Domain

Product page: <https://www.linknewnet.com/products/air-ap3802i-s-k9>

Quick Specifications

Attribute	Value
Indicators	Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors
Dimensions (W x L x H)	8.66 x 8.68 x 2.46 in. (22 x 22 x 6.25 cm),
Weight	4.6 lb (2.09 kg)
Input power requirements	802.3at PoE+, Cisco Universal Power over Ethernet (Cisco UPOE) 802.3at power injector (AIR-PWRINJ6=) 50W power supply (AIR-PWR-50=)
Power draw	30W at the PSE with all features enabled except for the USB 2.0 port 34W at the PSE with the USB 2.0 port enabled
System memory	1024 MB DRAM 256 MB Flash
Warranty	Limited lifetime hardware warranty
Product Code	AIR-AP3802I-S-K9
Brand	CISCO

Replacement / Alternative Options

If the AIR-AP3802I-S-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
AIR-AP-BRACKET-9=	C9130AXE antenna bracket
AIR-AP1041N-A-K9	Cisco 1040 Access Point AIR-AP1041N-A-K9 802.11g/n Fixed Auto AP; Int Ant; A Reg Domain

Request availability: [Ask for current stock](#) of AIR-AP3802I-S-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).