

Cisco AIR-CAP1532I-M-K9 802.11n Low-Profile Outdoor AP, Internal Ant., M Reg Dom

Model: AIR-CAP1532I-M-K9 | Brand: CISCO

Product Overview

Cisco AIR-CAP1532I-M-K9 802.11n Low-Profile Outdoor AP, Internal Ant., M Reg Dom

Product page: <https://www.linknewnet.com/products/air-cap1532i-m-k9>

Quick Specifications

Attribute	Value
Model	AIR-CAP1532I-M-K9
Brand	Cisco
Product Category	Wireless Access Points
Standard Supported	IEEE 802.11a/b/g/n
Frequency Band	2.4 GHz, 5 GHz
Antenna Type	Internal Antenna
Regulatory Domain	M (USA)
Maximum Data Rate	300 Mbps
Transmit Power	Up to 28 dBm
Ethernet Ports	2 x 10/100/1000 Base-T Ethernet (RJ-45)
PoE Support	Yes, 802.3af/802.3at
Mounting Options	Wall, Pole
Operating Temperature	-40■■■C to 65■■■C (-40■■■F to 149■■■F)
Dimensions (W x D x H)	218 x 171 x 56 mm (8.58 x 6.73 x 2.20 inches)
Power Source	AC Power, PoE
Enclosure Rating	IP67
Management Protocols	HTTP, SNMP, Telnet, SSH
Security Features	WPA/WPA2, 802.1X, AES
Indicator Lights	Power, Ethernet, 2.4 GHz, 5 GHz
Warranty	Limited Lifetime Warranty
Product Code	AIR-CAP1532I-M-K9
Brand	CISCO

Replacement / Alternative Options

If the AIR-CAP1532I-M-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
AIR-CAB005PL-R	Antenna Cable 5 ft low loss plenum cable, RP-TNC connectors
AIR-CAB020DRG6-F	Cisco AP Accessory AIR-CAB020DRG6-F 20 ft Dual RG-6 Cable Assembly w/F-Type Connectors Spare

Request availability: [Ask for current stock](#) of AIR-CAP1532I-M-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).