

Cisco AIR-CAP1532I-Q-K9 802.11n Low-Profile Outdoor AP, Internal Ant., Q Reg Dom.

Model: AIR-CAP1532I-Q-K9 | Brand: CISCO

Product Overview

Cisco AIR-CAP1532I-Q-K9 802.11n Low-Profile Outdoor AP, Internal Ant., Q Reg Dom.

Product page: <https://www.linknewnet.com/products/air-cap1532i-q-k9>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	AIR-CAP1532I-Q-K9
Frequency Band	2.4 GHz and 5 GHz
Wireless Standard	802.11n
Antenna	Internal
Operating Temperature	-40■■■C to 55■■■C
Maximum Data Rate	300 Mbps
Ethernet Ports	1x 10/100/1000 Ethernet
Dimensions	580 x 580 x 224 mm
Security	WPA2, WPA, 802.11i
Power Options	Power over Ethernet (PoE)
Mounting Options	Pole and wall mountable
MIMO	3x3 MIMO
Environmental Compliance	IP67 Rated
Max Power Consumption	12.95W
Regulation Domain	Q (Reg Dom)
Humidity	10% to 90% (non-condensing)
LED Indicators	Yes
Encryption	128-bit AES
Max Clients	128 clients per radio
Product Code	AIR-CAP1532I-Q-K9
Brand	CISCO

Replacement / Alternative Options

If the AIR-CAP1532I-Q-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
AIR-CAB005PL-R	Antenna Cable 5 ft low loss plenum cable, RP-TNC connectors
AIR-CAB020DRG6-F	Cisco AP Accessory AIR-CAB020DRG6-F 20 ft Dual RG-6 Cable Assembly w/F-Type Connectors Spare

Request availability: [Ask for current stock](#) of AIR-CAP1532I-Q-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).