

AIR-CAP2702I-D-K9 - Cisco 2700 Series Access Points

Model: AIR-CAP2702I-D-K9 | Brand: CISCO

Product Overview

802.11ac CAP w/CleanAir; 3x4:3SS; Int Ant; D Reg Domain

Product page: <https://www.linknewnet.com/products/air-cap2702i-d-k9>

Quick Specifications

Attribute	Value
Model	AIR-CAP2702I-D-K9
Product Series	Cisco Aironet 2700 Series
Operating Frequency	2.4 GHz and 5 GHz
Wi-Fi Standards	802.11ac
Data Rates Supported	Up to 1.3 Gbps
Ethernet Ports	2 x 10/100/1000 BASE-T
Max Clients Supported	200 clients
Encryption Types	WPA/WPA2-PSK, WPA/WPA2-Enterprise
Antenna Type	Internal
MIMO Technology	3x4 MIMO
Modulation	QPSK, 16-QAM, 64-QAM, 256-QAM
Management	Yes
Deployment Options	Controller-based
Power Options	PoE, AC Adapter
Power Consumption	15.4W
Operating Temperature	0°C to 40°C
Humidity	10% to 90% non-condensing
Mounting Options	Ceiling, Wall
Dimensions	22 x 22 x 6 cm
Warranty	Limited Lifetime
Product Code	AIR-CAP2702I-D-K9
Brand	CISCO

Replacement / Alternative Options

If the AIR-CAP2702I-D-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
AIR-CAB005PL-R	Antenna Cable 5 ft low loss plenum cable, RP-TNC connectors
AIR-CAB020DRG6-F	Cisco AP Accessory AIR-CAB020DRG6-F 20 ft Dual RG-6 Cable Assembly w/F-Type Connectors Spare

Request availability: [Ask for current stock](#) of AIR-CAP2702I-D-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).