

# AIR-CAP3502E-I-K9 Cisco 3500e Series Access Point

Model: AIR-CAP3502E-I-K9 | Brand: CISCO

## Product Overview

Cisco 3500e AP AIR-CAP3502E-I-K9 802.11a/g/n Ctrlr-based AP w/CleanAir; Ext Ant; I Reg Domain

Product page: <https://www.linknewnet.com/products/air-cap3502e-i-k9>

## Quick Specifications

| Attribute              | Value                                                                                             |
|------------------------|---------------------------------------------------------------------------------------------------|
| Model                  | AIR-CAP3502E-I-K9                                                                                 |
| Brand                  | Cisco                                                                                             |
| Wireless Standards     | 802.11a/g/n                                                                                       |
| Regulatory Domain      | I [India]                                                                                         |
| Controller-based       | Yes                                                                                               |
| CleanAir Technology    | Yes                                                                                               |
| Antenna Type           | External Antennas                                                                                 |
| Radio                  | Dual radio, 2.4 GHz and 5 GHz                                                                     |
| Ethernet Ports         | 1 x 10/100/1000BASE-T autosensing (RJ-45)                                                         |
| Power Options          | 802.3af Ethernet switch/PoE, Cisco power injector, local power supply (Cisco PWRINJ4 recommended) |
| Max Data Rate          | Up to 450 Mbps                                                                                    |
| Console Port           | RJ-45                                                                                             |
| Max Associated Clients | 128 per radio                                                                                     |
| Dimensions             | 8.7 x 8.7 x 1.84 inches (22.1 x 22.1 x 4.7 cm)                                                    |
| Operating Temperature  | 32° to 104°F (0° to 40°C)                                                                         |
| LED Indicators         | Status, Ethernet, Radio                                                                           |
| Mounting               | Ceiling, wall                                                                                     |
| Compliance             | FCC Part 15, RSS-210 (Canada), EN 300.328, EN 301.489-1, EN 301.893 (Europe), ARIB-STD 66 (Japan) |
| Warranty               | Limited lifetime hardware warranty                                                                |
| Product Code           | AIR-CAP3502E-I-K9                                                                                 |
| Brand                  | CISCO                                                                                             |

## Replacement / Alternative Options

If the AIR-CAP3502E-I-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

| Model                            | Specification                                                                                |
|----------------------------------|----------------------------------------------------------------------------------------------|
| <a href="#">AIR-CAB005PL-R</a>   | Antenna Cable 5 ft low loss plenum cable, RP-TNC connectors                                  |
| <a href="#">AIR-CAB020DRG6-F</a> | Cisco AP Accessory AIR-CAB020DRG6-F 20 ft Dual RG-6 Cable Assembly w/F-Type Connectors Spare |

Request availability: [Ask for current stock](#) of AIR-CAP3502E-I-K9 or its alternatives.

## **Buying from LinkNewNet**

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).