

# AIR-LAP1131AG-I-K9 1130AG Series Access Points

Model: AIR-LAP1131AG-I-K9 | Brand: CISCO

## Product Overview

802.11ag LWAPP AP Integrated Antennas Israel Cnfg 1130AG Series Access Points

Product page: <https://www.linknewnet.com/products/air-lap1131ag-i-k9>

## Quick Specifications

| Attribute                | Value                                                                                                                              |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Part Number              | AIR-LAP1131AG-I-K9                                                                                                                 |
| Product Description      | 802.11ag LWAPP AP Integrated Antennas Israel Cnfg 1130AG Series Access Points                                                      |
| Software                 | • Cisco IOS Software Release 12.3(8)JA or later (autonomous). • Cisco IOS Software Release 12.3(11)JX or later (Lightweight Mode). |
| Data Rates Supported     | • 802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps • 802.11g: 1, 2, 5.5, 6, 9, 11, 12, 18, 24, 36, 48, and 54 Mbps                   |
| Network Standard         | IEEE 802.11a, 802.11b, and 802.11g                                                                                                 |
| Uplink                   | Autosensing 802.3 10/100BASE-T Ethernet                                                                                            |
| Nonoverlapping Channels  | 802.11a: Up to 19 802.11b/g: 3                                                                                                     |
| Range                    | Indoor (Distance Across Open Office Environment): Outdoor:                                                                         |
| Antennas                 | • 2.4 GHz • Gain 3.0 dBi • Horizontal Beamwidth 360° • 5 GHz • Gain 4.5 dBi • Horizontal Beamwidth 360°                            |
| Dimensions (H x W x D)   | 7.5 in. x 7.5 in. x 1.3 in. (19.1 x 19.1 x 3.3 cm)                                                                                 |
| Weight                   | 1.5 lb (0.67 kg)                                                                                                                   |
| System Memory            | • 32 MB RAM • 16 MB FLASH                                                                                                          |
| Input Power Requirements | • 100-240 VAC; 50-60Hz (power supply) • 36-57 VDC (device)                                                                         |
| Power Draw               | 12.2W maximum                                                                                                                      |
| Product Code             | AIR-LAP1131AG-I-K9                                                                                                                 |
| Brand                    | CISCO                                                                                                                              |

## Replacement / Alternative Options

If the AIR-LAP1131AG-I-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

| Model                             | Specification                                                                               |
|-----------------------------------|---------------------------------------------------------------------------------------------|
| <a href="#">AIR-LAP1041N-A-K9</a> | Cisco 1040 Access Point AIR-LAP1041N-A-K9 802.11g/n Fixed Unified AP; Int Ant; A Reg Domain |
| <a href="#">AIR-LAP1041N-E-K9</a> | Cisco 1040 Access Point AIR-LAP1041N-E-K9 802.11g/n Fixed Unified AP; Int Ant; E Reg Domain |

Request availability: [Ask for current stock](#) of AIR-LAP1131AG-I-K9 or its alternatives.

## Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).