

AIR-PWRINJ1500-2 Cisco Access Point power option

Model: AIR-PWRINJ1500-2 | Brand: CISCO

Product Overview

Cisco AP power option AIR-PWRINJ1500-2 1520 Series Power Injector

Product page: <https://www.linknewnet.com/products/air-pwrinj1500-2>

Quick Specifications

Attribute	Value
Input voltage	100 to 240 VAC
Output voltage	56.0 VDC
Voltage range tolerance	54 VDC to 57 VDC
Maximum current	1.43 A
No load current	15 mA
Output 1 voltage and current	56VDC@0.71A Pin 3, 6—+56VDC Pin 1, 2—Return
Output 2 voltage and current	56VDC@0.71A Pin 4, 5—+56VDC Pin 7, 8—Return
Operating temperature	-40 to 131 °F (-40 to 55 °C)
Storage temperature	-58 to 185 °F (-50 to 85 °C)
Operating humidity	10% to 90% non-condensing
Storage humidity	10% to 95% non-condensing
Length	8 in.(20.3 cm)
Width	4.25 in.(10.8 cm)
Height	2.5 in. (6.3 cm)
Product Code	AIR-PWRINJ1500-2
Brand	CISCO

Replacement / Alternative Options

If the AIR-PWRINJ1500-2 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
AIR-PWR-B	Cisco AP power option AIR-PWR-B PwrSpplly:100-240VAC,48VDC:AP1130,1140,1240,1260,1300,3500
AIR-PWR-B	Cisco AP power option AIR-PWR-B PwrSpplly:100-240VAC,48VDC:AP1130,1140,1240,1260,1300,3500

Request availability: [Ask for current stock](#) of AIR-PWRINJ1500-2 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).