

# AIR-SAP2602I-E-K9 Cisco Aironet 2600 Series Access Points

Model: AIR-SAP2602I-E-K9 | Brand: CISCO

## Product Overview

Cisco Aironet 2600 AP AIR-SAP2602I-E-K9 802.11n Auto ; 3x4:3SS; Mod ; Int Ant ; E Reg Domain

Product page: <https://www.linknewnet.com/products/air-sap2602i-e-k9>

## Quick Specifications

| Attribute                | Value                                                                                                                                               |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Software                 | Cisco Unified Wireless Network Software Release 7.2.110 or later.                                                                                   |
| Data Rates Supported     | 802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps                                                                                                      |
| Integrated Antenna       | ● 2.4 GHz, Gain 4 dBi, internal omnidirectional, horizontal beamwidth 360° ● 5 GHz, Gain 4 dBi, internal omnidirectional, horizontal beamwidth 360° |
| Interfaces               | ● 10/100/1000BASE-T autosensing (RJ-45) ● Management console port (RJ-45)                                                                           |
| Indicators               | ● Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors                           |
| Dimensions (W x L x H)   | ● Access point (without mounting bracket): 8.69x8.69x2.11in. (22.1x22.1x5.4)                                                                        |
| Weight                   | ● 2.3 lbs (1.04 kg) (2.7 lbs for external)                                                                                                          |
| System Memory            | ● 256 MB DRAM ● 32 MB flash                                                                                                                         |
| Input Power Requirements | ● AP2600: 44 to 57 VDC ● Power Supply and Power Injector: 100 to 240 VAC; 50 to 60 Hz                                                               |
| Powering Options         | ● 802.3af Ethernet Switch ● Cisco AP2600 Power Injectors (AIR-PWRINJ4=) ● Cisco AP2600 Local Power Supply (AIR-PWR-B=)                              |
| Warranty                 | Limited Lifetime Hardware Warranty                                                                                                                  |
| Product Code             | AIR-SAP2602I-E-K9                                                                                                                                   |
| Brand                    | CISCO                                                                                                                                               |

## Replacement / Alternative Options

If the AIR-SAP2602I-E-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

| Model                                    | Specification                                                                             |
|------------------------------------------|-------------------------------------------------------------------------------------------|
| <a href="#">AIR-SAP1602E-A-K9 (USED)</a> | 802.11a/g/n Stand-Alone AP, Ext Ant, A Reg Domain Cisco Aironet 1600 Series Access Points |
| <a href="#">AIR-SAP1602E-A-K9</a>        | 802.11a/g/n Stand-Alone AP, Ext Ant, A Reg Domain Cisco Aironet 1600 Series Access Points |

Request availability: [Ask for current stock](#) of AIR-SAP2602I-E-K9 or its alternatives.

## Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).