

AIR-AP1832I-Q-K9 - Cisco Aironet 1832i Access Point

Model: AIR-AP1832I-Q-K9 | Brand: CISCO

Product Overview

802.11ac Wave 2 AP, 3x3:2, Internal Antenna, Q Regulatory Domain

Product page: <https://www.linknewnet.com/products/ap-air-ap1832i-q-k9>

Quick Specifications

Attribute	Value
Deployment modes	Centralized, standalone, sniffer,** Cisco FlexConnect®, monitor,** OfficeExtend,** mesh**
Data rates supported	802.11a: 6, 9, 12, 18, 24, 36, 48, and 54 Mbps
MCS index	GI = 800 ns GI = 800 ns GI = 400 ns GI = 400 ns
	20-MHz rate (Mbps) 40-MHz rate (Mbps) 20-MHz rate (Mbps) 40-MHz rate (Mbps)
0	6.5 13.5 7.2 15
1	13 27 14.4 30
2	19.5 40.5 21.7 45
3	26 54 28.9 60
4	39 81 43.3 90
5	52 108 57.8 120
6	58.5 121.5 65 135
7	65 135 72.2 150
8	13 27 14.4 30
9	26 54 28.9 60
10	39 81 43.3 90
11	52 108 57.8 120
12	78 162 86.7 180
13	104 216 115.6 240
14	117 243 130 270
15	130 270 144.4 300
Product Code	AIR-AP1832I-Q-K9
Brand	CISCO

Replacement / Alternative Options

If the AIR-AP1832I-Q-K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
AIR-AP-BRACKET-9=	C9130AXE antenna bracket

AIR-AP1041N-A-K9	Cisco 1040 Access Point AIR-AP1041N-A-K9 802.11g/n Fixed Auto AP; Int Ant; A Reg Domain
----------------------------------	---

Request availability: [Ask for current stock](#) of AIR-AP1832I-Q-K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).