

# AIRAP1832I-AK910C - Cisco Aironet 1832i Access Point

Model: AIRAP1832I-AK910C | Brand: CISCO

## Product Overview

Cisco Aironet 1830 Series 10-pack with Mobility Expre, A Regulatory Domain

Product page: <https://www.linknewnet.com/products/ap-airap1832i-ak910c-cisco>

## Quick Specifications

| Attribute                | Value                                                                                                                                                |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Software                 | Cisco Unified Wireless Network Software Release with AireOS wireless controllers: 8.1.121.0 or later for the Cisco Aironet 1830 Series Access Points |
| Deployment modes         | Centralized, standalone, sniffer, Cisco FlexConnect <sup>™</sup> , monitor, OfficeExtend, mesh                                                       |
| Integrated antenna       | 2.4 GHz, gain 3 dBi, internal omni, horizontal beamwidth 360° 5 GHz, gain 5 dBi, internal omni, horizontal beamwidth 360°                            |
| Interfaces               | 1 x 10/100/1000BASE-T autosensing (RJ-45), Power over Ethernet (PoE) Management console port (RJ-45) USB 2.0 (enabled via future software)           |
| Indicators               | Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors                              |
| Dimensions (W x L x H)   | Access point (without mounting bracket): 8.3 x 8.3 x 2 in. (210.8 x 210.8 x 50.8 mm)                                                                 |
| Weight                   | 3.12 lb (1.41 kg)                                                                                                                                    |
| System memory            | 1 GB DRAM 256 MB flash                                                                                                                               |
| Input power requirements | AP1830: 44 to 57 VDC Power supply and power injector: 100 to 240 VAC; 50 to 60 Hz                                                                    |
| Warranty                 | Limited lifetime hardware warranty                                                                                                                   |
| Product Code             | AIRAP1832I-AK910C                                                                                                                                    |
| Brand                    | CISCO                                                                                                                                                |

## Replacement / Alternative Options

If the AIRAP1832I-AK910C is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

| Model                              | Specification                                                                       |
|------------------------------------|-------------------------------------------------------------------------------------|
| <a href="#">AIRAP1572EACBK9-RF</a> | 802.11ac Outdoor AP, External Antenna, ACpower, B Regulatory Domain, Remanufactured |
| <a href="#">AIRAP1572EACEK9-RF</a> | 802.11ac Outdoor AP, External Antenna, ACpower, E Regulatory Domain, Remanufactured |

Request availability: [Ask for current stock](#) of AIRAP1832I-AK910C or its alternatives.

## Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).