

AIRAP1852I-AK910C - Cisco Aironet 1852i Access Point

Model: AIRAP1852I-AK910C | Brand: CISCO

Product Overview

Cisco Aironet 1850i Series 10-pack with Mobility Expre, A Regulatory Domain

Product page: <https://www.linknewnet.com/products/ap-airap1852i-ak910c>

Quick Specifications

Attribute	Value
Description	Cisco Aironet 1850i Series 10-pack with Mobility Expre, A Regulatory Domain
Software	Cisco Unified Wireless Network Software Release with AireOS wireless controllers: 8.1 MR1 or later for the Cisco Aironet 1850 Series Access Points
Deployment modes	Centralized local, Standalone, Sniffer, Cisco FlexConnect, Monitor, OfficeExtend, Mesh
Integrated antenna	2.4 GHz, gain 3 dBi, internal omni, horizontal beamwidth 360° 5 GHz, gain 5 dBi, internal omni, horizontal beamwidth 360°
Indicators	Status LED indicates boot loader status, association status, operating status, boot loader warnings, boot loader errors
Dimensions (W x L x H)	Access point (without mounting bracket): 8.3 x 8.3 x 2 in. (210.8 x 210.8 x 50.8 mm)
Weight	3.12 lb (1.41 kg)
System memory	1 GB DRAM 256 MB flash
Input power requirements	AP1850: 44 to 57 VDC Power supply and power injector: 100 to 240 VAC; 50 to 60 Hz
Warranty	Limited lifetime hardware warranty
Product Code	AIRAP1852I-AK910C
Brand	CISCO

Replacement / Alternative Options

If the AIRAP1852I-AK910C is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
AIRAP1572EACBK9-RF	802.11ac Outdoor AP, External Antenna, ACpower, B Regulatory Domain, Remanufactured
AIRAP1572EACEK9-RF	802.11ac Outdoor AP, External Antenna, ACpower, E Regulatory Domain, Remanufactured

Request availability: [Ask for current stock](#) of AIRAP1852I-AK910C or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).