

901-P300-WW01 Access Point

Model: Ruckus 901-P300-WW01 | Brand: CISCO

Product Overview

Outdoor point-to-point and point-to-multi point bridge that unleashes the promise of 5GHz 802.11ac, delivering unparalleled throughput.

Product page: <https://www.linknewnet.com/products/ap-ruckus-901-p300-ww01>

Quick Specifications

Attribute	Value
Product Type	Outdoor Point-to-Point and Point-to-Multi Point Bridge
Frequency Band	5GHz
Standard	802.11ac
Data Transfer Rate	Up to 867 Mbps
Antenna Gain	14 dBi
Range	Up to 12 Km
Network Ports	1x 10/100/1000 Mbps Ethernet
Encryption	WPA-PSK, WPA-TKIP, WPA2 AES
Weatherproof Rating	IP67
Power Consumption	13W (typical), 18W (maximum)
Power Supply	IEEE 802.3af Power over Ethernet (PoE)
Operating Temperature	-40°C to 65°C
Security Standards	802.11i, 802.1x
Operating Humidity	Up to 95% non-condensing
Mounting Options	Pole, Wall
Dimensions	234 x 184 x 77 mm
Indicator LEDs	Power, Ethernet, Wireless Link
Compliance	CE, FCC, IC
Management	Web GUI, SNMP
MIMO Technology	2x2:2
Product Code	Ruckus 901-P300-WW01
Brand	CISCO

Replacement / Alternative Options

If the Ruckus 901-P300-WW01 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC
-----------	---

Request availability: [Ask for current stock](#) of Ruckus 901-P300-WW01 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).