

ASA5540-K8 - Cisco ASA 5540 Adaptive Security Appliance

Model: ASA5540-K8 | Brand: CISCO

Product Overview

ASA 5540 Security Appliance with SW, HA, 4GE+1FE, DES, Cisco ASA 5500 Series Firewall Edition Bundles

Product page: <https://www.linknewnet.com/products/asa5540-k8>

Quick Specifications

Attribute	Value
Product Brand	Cisco
Product Name	ASA5540-K8 (USED)
Product Type	Security Appliance
Software Included	Cisco ASA 5500 Series Firewall Edition Bundles
High Availability	Supported
Network Interfaces	4 x GE, 1 x Fast Ethernet (FE)
Encryption Algorithm	DES
Form Factor	Rack-mountable
Dimensions	Length x Width x Height
Power Supply	AC 100-240 V (50/60 Hz)
Max Power Consumption	550 Watts
Operating Temperature	32°F to 104°F (0°C to 40°C)
Storage Temperature	-13°F to 158°F (-25°C to 70°C)
Humidity	5% to 95% (Non-condensing)
Firewall Throughput	650 Mbps
VPN Throughput	325 Mbps
Concurrent Sessions	400,000
VPN Peers	5,000
Security Contexts	Up to 50
Management	CLI, ASDM
Product Code	ASA5540-K8
Brand	CISCO

Replacement / Alternative Options

If the ASA5540-K8 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ASA5540-AIP20-K8	ASA 5540 Security Appliance w/ AIP-SSM-20, SW, HA, 4GE+1FE, DES, Cisco ASA 5500 Series IPS Edition Bundles

ASA5540-AIP20-K9	ASA 5540 Security Appliance w/ AIP-SSM-20, SW, HA, 4GE+1FE, 3DES/AES, Cisco ASA 5500 Series IPS Edition Bundles
------------------	---

Request availability: [Ask for current stock](#) of ASA5540-K8 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).