

ASR-9010-AC - Cisco ASR 9010 Series Chassis

Model: ASR-9010-AC | Brand: CISCO

Product Overview

Cisco ASR 9010 Chassis ASR-9010-AC ASR-9010 AC Chassis

Product page: <https://www.linknewnet.com/products/asr-9010-ac>

Quick Specifications

Attribute	Value
Description	Cisco ASR 9010 Chassis, ASR-9010-AC, ASR-9010 AC Chassis
Slot orientation	Vertical
Cisco ASR 9000 Series RSP	Dual redundant RSPs with integrated fabric in 2 slots
Cisco ASR 9000 Series line cards	8 line-card slots
“Commons” components	2 RSPs 2 fan trays 2 PEMs (either DC or AC) 1 fan filter
Reliability and availability	Fabric redundancy Fan redundancy Feed redundancy Power-supply redundancy RSP redundancy Software redundancy
Rack mounting	19-in. default 21- and 23-in. adapters available Note: Minimum 17.75-in. opening between posts is needed for proper operation
Cabinet mounting	Yes Note: Doors not recommended in enclosed cabinets
Wall mounting	No
Airflow	Front-to-back
Thermal	Two fan trays: ● 12 high-efficiency fans per tray ● Variable-speed fans for optimal thermal performance ● No single point of failure
Redundancy	● AC: N+N redundancy ● DC: N+1 redundancy ● Power module redundancy ● A/B Feed redundancy ● PEM redundancy
Power zones	No power zone restrictions Fully load-sharing power infrastructure
Power input	Worldwide ranging AC (200-240V; 50-60 Hz; 16A maximum) Worldwide ranging DC (-40 to -72V; 50A nominal, 60A maximum)
Power-module airflow	Front-to-back
Product Code	ASR-9010-AC
Brand	CISCO

Replacement / Alternative Options

If the ASR-9010-AC is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ASR-9000V-AC	Cisco ASR 9000v Router
ASR-9001	ASR 9001 Router with 4 x 10 GE

Request availability: [Ask for current stock](#) of ASR-9010-AC or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).