

ASR1000-ESP200-X - Cisco ASR 1000 Series Embedded Services Processor

Model: ASR1000-ESP200-X | Brand: CISCO

Product Overview

Cisco ASR1000 Embedded Services Processor X, 200G
Product page: <https://www.linknewnet.com/products/asr1000-esp200-x>

Quick Specifications

Attribute	Value
Model	ASR1000-ESP200-X
Product Type	Embedded Services Processor
Processing Throughput	200 Gbps
Form Factor	Plug-in module
Compatibility	Cisco ASR 1000 Series Aggregation Services Routers
Interfaces	Supports various interface modules
Memory	8 GB DRAM
Network Processor	Cisco Flow Processor
Max Power Consumption	500W
Redundancy	1+1 Redundancy Support
Operating Temperature	32 to 104°F (0 to 40°C)
Operating Humidity	5% to 85% RH
Storage Temperature	-40 to 158°F (-40 to 70°C)
Storage Humidity	5% to 95% RH
Security	Embedded security features
MTBF	750,000 hours
Dimensions	1.75 in. x 16.9 in. x 17.1 in.
Cooling	Front-to-back airflow
Compliance	RoHS, CE, UL
Product Code	ASR1000-ESP200-X
Brand	CISCO

Replacement / Alternative Options

If the ASR1000-ESP200-X is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ASR1000-2T+20X1GE=	ASR1000 2-port 10GE. 20-port GE Line Card
ASR1000-6TGE=	ASR1000 6 port 10 GE Line Card

Request availability: [Ask for current stock](#) of ASR1000-ESP200-X or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).