

Cisco Router ASR 1000 Series ASR1009-X

Model: ASR1009-X | Brand: CISCO

Product Overview

The ASR1009-X is the router chassis for the Cisco ASR1009.

Product page: <https://www.linknewnet.com/products/asr1009-x>

Quick Specifications

Attribute	Value
Default memory	8-GB DRAM RP2 8-GB DRAM RP3
Shared port adapters	12 SPA slots
Ethernet port adapters	6 EPA slots
Cisco ASR 1000 Series ESP	2 ESP slots
Route processor	2 route-processor slots
Redundancy	Hardware: Yes
Built-in Gigabit Ethernet ports	0
Built-in 10 Gigabit Ethernet port	No
Network interface module	No
Cisco ASR 1000 Series	Cisco ASR 1009-X
ESP bandwidth	40 to 200 Gbps
Rack-mounting	Yes: 19-inch
Wall-mounting	No
External USB flash memory	1-GB USB flash-memory support
Power input	Worldwide ranging AC input range (85 to 264 VAC) Worldwide ranging DC (-40 to -72; -48V nominal)
Power consumption	● Maximum (DC): 5200W ● Maximum (AC): 5100W ● Maximum (out): 4575W
Airflow	Front-to-back
Product Code	ASR1009-X
Brand	CISCO

Replacement / Alternative Options

If the ASR1009-X is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ASR1000-2T+20X1GE=	ASR1000 2-port 10GE. 20-port GE Line Card
ASR1000-6TGE=	ASR1000 6 port 10 GE Line Card

Request availability: [Ask for current stock](#) of ASR1009-X or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).