

ASR920-24SZ-M - Cisco ASR 920 Series

Model: ASR920-24SZ-M | Brand: CISCO

Product Overview

Cisco ASR920 Series - 24GE Fiber and 4-10GE : Modular PSU

Product page: <https://www.linknewnet.com/products/asr920-24sz-m>

Quick Specifications

Attribute	Value
Rack mounts	ETSI rack-mount kit 19-in. rack-mount kit 23-in. rack-mount kit
Power consumption	Max 145W, Typical: 110W
AC input voltage and frequency	Voltage range: 85V AC to 264V AC, nominal 100V AC to 240V AC Frequency Range: 47 to 63 Hz, nominal 50 to 60 Hz
DC input voltage	Voltage range: -18 to -32 VDC or -36 to -72 VDC, nominal: -24 VDC/-48 VDC
Relative humidity	5 to 95 percent, noncondensing
Storage environment	Temperature: -40 to 70°C altitude: 15,000 feet (4570m)
Seismic	Zone 4
Safety	● UL 60950-1, 2005 ● CAN/CSA C22.2 No. 60950-1: 2005 ● IEC 60950-1, 2005 ● EN 60950-1, 2005 ● AS/NZS 60950.1:2005
Electromagnetic	● FCC CFR47 Part 15 Class A
Emissions compliance	● EN55022, class A ● CISPR22, class A ● ICES-003, class A ● EN 300 386, class A ● VCCI, class A ● KN22, class A ● EN61000-3-2 to EN61000-3-3
Power substation system compliance	● IEC-61850-3 (2002) (ASR-920-12SZ-IM) ● IEEE1613 (2009) (ASR-920-12SZ-IM)
NEBS1	● GR-63-CORE ● GR-1089-CORE ● SR-3580 NEBS Level 4
ETSI	● ETS/EN 300 119 Part 4 ● ETS/EN 300 019 - Storage: Class 1.2, Transportation: Class 2.3, In-Use/Operational: Class 3.2 ● ETS/EN 300 753
Product Code	ASR920-24SZ-M
Brand	CISCO

Replacement / Alternative Options

If the ASR920-24SZ-M is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module
WS-C4948E	Cisco Catalyst 4948E, opt sw, 48-Port 10/100/1000+ 4 SFP+, INCLUDES DUAL AC

Request availability: [Ask for current stock](#) of ASR920-24SZ-M or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).