

Cisco Router ISR 4000 Series C1-CISCO4221/K9

Model: C1-CISCO4221/K9 | Brand: CISCO

Product Overview

Cisco One -Cisco ISR 4221 (2GE, 2NIM, 8G FLASH, 4G DRAM, IPB)

Product page: <https://www.linknewnet.com/products/c1-cisco4221-k9>

Quick Specifications

Attribute	Value
Aggregate Throughput	35 Mbps to 75 Mbps
RJ-45-based ports	2
SFP-based ports	1
Enhanced service-module slots	0
Doublewide service-module slots	0
NIM slots	2
Default flash memory	8 GB
Maximum flash memory	8 GB
External USB 2.0 slots (type A)	1
Power-supply options	External: AC Only
AC input voltage	100 to 240 VAC autoranging
AC input frequency	47 to 63 Hz
AC input surge current	90 A peak and less than 3 Arms per half cycle
Typical power (no modules) (watts)	24
Product Code	C1-CISCO4221/K9
Brand	CISCO

Replacement / Alternative Options

If the C1-CISCO4221/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C1-CISCO1921/K9	Cisco ONE - ISR 1921, ideal for scalable and secure network configurations, high performance.
C1-CISCO1941/K9	Cisco ONE - ISR 1941, a versatile platform for diverse networking needs, offering robust performance.

Request availability: [Ask for current stock](#) of C1-CISCO4221/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).