

Cisco Router ISR 4000 Series C1-CISCO4351/K9

Model: C1-CISCO4351/K9 | Brand: CISCO

Product Overview

Cisco ONE ISR 4351 (3GE.3NIM.2SM.4G FLASH.4G DRAM.IPB)

Product page: <https://www.linknewnet.com/products/c1-cisco4351-k9>

Quick Specifications

Attribute	Value
Product Number	C1-CISCO4351/K9
Product Description	Cisco ONE ISR 4351 (3GE.3NIM.2SM.4G FLASH.4G DRAM.IPB)
Aggregate Throughput	200 Mbps to 400 Mbps
RJ-45-based ports	3
SFP-based ports	3
Enhanced service-module slots	2
Doublewide service-module slots	1 (assumes no singlewide SM-X modules installed)
NIM slots	3
OIR (all I/O modules)	Yes
Onboard ISC slot	1
Default flash memory	4 GB
Maximum flash memory	16 GB
External USB 2.0 slots (type A)	2
Power-supply options	Internal: AC, DC, and PoE
Redundant power supply	N/A
AC input voltage	100 to 240 VAC autoranging
AC input frequency	47 to 63 Hz
AC input surge current	60 A peak and less than 12 Arms per half cycle
Typical power (no modules) (watts)	48
Product Code	C1-CISCO4351/K9
Brand	CISCO

Replacement / Alternative Options

If the C1-CISCO4351/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C1-CISCO1921/K9	Cisco ONE - ISR 1921, ideal for scalable and secure network configurations, high performance.

C1-CISCO1941/K9	Cisco ONE - ISR 1941, a versatile platform for diverse networking needs, offering robust performance.
-----------------	---

Request availability: [Ask for current stock](#) of C1-CISCO4351/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).