

Cisco ONE Catalyst 4500 Series Platform

C1-X45-SUP8-E/2

Model: C1-X45-SUP8-E/2 | Brand: CISCO

Product Overview

C1-X45-SUP8-E/2 Cisco One Catalyst 4500 E-Series Redundant Supervisor 8-E

Product page: <https://www.linknewnet.com/products/c1-x45-sup8-e-2>

Quick Specifications

Attribute	Value
Parent Product Data	FE: - switch, FE: Cisco - switch, FE: NULL - switch
Type	Switched virtual interfaces (SVIs)
Value	10000
Supported Flash Memory Cards	SD Memory Card
Installed Size	4 GB
Technology	SDRAM
Form Factor	Plug-in module
Connectivity Technology	Wired
Compliant Standards	IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ad (LACP), IEEE 802.3ae, IEEE 802.3az
Routing Protocol	PIM-DM, PIM-SM, PIM-SSM
Qty	8
Connector Type	Type A
Min Operating Temperature	32 °F
Max Operating Temperature	104 °F
Humidity Range Operating	10 - 90% (non-condensing)
Model	Supervisor Engine 8-E Redundant
Clock Speed	2.2 GHz
Product Code	C1-X45-SUP8-E/2
Brand	CISCO

Replacement / Alternative Options

If the C1-X45-SUP8-E/2 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C1-X45-SUP7L-E/2	Cisco One Catalyst 4500 E-Series Supervisor LE, 520Gbps red
C1-X45-SUP7L-E	Cisco One Catalyst 4500 E-Series Supervisor 7 LE, 520Gbps

Request availability: [Ask for current stock](#) of C1-X45-SUP8-E/2 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).