

C1109-2PLTEGB - Cisco Router ISR 1100 Series

Model: C1109-2PLTEGB | Brand: CISCO

Product Overview

Cisco ISR1109-2P router, LTE, GB

Product page: <https://www.linknewnet.com/products/c1109-2pltegb>

Quick Specifications

Attribute	Value
Description	Cisco ISR1109-2P router, LTE, GB
WAN GE	1
WAN GE/SFP combo	N/A
ADSL2/VDSL2+	N/A
LTE Advanced (CAT6)	N/A
802.11ac	N/A
LAN GE	2
PoE or PoE+	N/A
Integrated USB 3.0 AUX/console	Yes (No AUX)
Pluggable	N/A Same CAT4 technology as PLTE-GB
Dimensions (H x W x D)	1.15 x 7.6 x 6.3 in. (29.2 x 193.0 x 160.0mm) (includes rubber feet models)
AC Power Input voltage	Universal 100 to 240 VAC
Frequency	50-60 Hz
Maximum output power	30W (default)
Output voltages	12 VDC
Console port	Micro USB console (USB 3.0)
Default and maximum DRAM	4GB
Default and maximum flash	4GB
Operating humidity	10% to 85% relative humidity (noncondensing)
Operating temperature	32° to 104°F (0° to 40°C)
Product Code	C1109-2PLTEGB
Brand	CISCO

Replacement / Alternative Options

If the C1109-2PLTEGB is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C1109-2PLTEUS	Cisco ISR1109-2P router, LTE, US
C1109-2PLTEVZ	Cisco ISR1109-2P router, LTE, VZ

Request availability: [Ask for current stock](#) of C1109-2PLTEGB or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).