

C1112-8P - Cisco Router ISR 1100 Series

Model: C1112-8P | Brand: CISCO

Product Overview

ISR 1100 G.FAST with GE SFP Ethernet Router

Product page: <https://www.linknewnet.com/products/c1112-8p>

Quick Specifications

Attribute	Value
Description	ISR 1100 G.FAST with GE SFP Ethernet Router
Dimensions (H x W x D)	1.75 x 12.7 x 9.03 in. (42 x 323 x 230mm)
Input voltage	Universal 100 to 240 VAC
Frequency	50-60 Hz
Maximum output power	66W (default)
Output voltages	12 VDC
PoE and PoE+	Single 150W power supply required for Cisco 1100-8P series router
External output voltage	48 VDC
GE	N/A
GE/SFP combo	1
ADSL2/VDSL2+	1 G.FAST (Annex B)
PoE	4
PoE+	2
Integrated USB 3.0 AUX/console	Yes
Default and maximum DRAM	4GB
Default and maximum flash	4GB
Operating humidity	10% to 85% relative humidity (noncondensing)
Operating temperature	32° to 104°F (0° to 40°C)
Nonoperating temperature	-4° to 149°F (-0° to 65°C)
Nonoperating humidity	5 to 95% relative humidity (noncondensing)
Product Code	C1112-8P
Brand	CISCO

Replacement / Alternative Options

If the C1112-8P is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C1112-8PLTEAWE	ISR 1112 8 Ports, E WiFi domain
C1112-8PLTEEA	ISR 1100 G.FAST GE SFP Router w/ LTE Adv SMS/GPS EMEA & NA

Request availability: [Ask for current stock](#) of C1112-8P or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).