

C2811-15UC-VSEC/K9 - Cisco 2800 Router

Model: C2811-15UC-VSEC/K9 | Brand: CISCO

Product Overview

2811 w/ PVDM2-32,AIM-CUE,15 CME/CUE/Ph lic,Adv IP,128F/512D

Product page: <https://www.linknewnet.com/products/c2811-15uc-vsec-k9>

Quick Specifications

Attribute	Value
Number of Ports:	2
Fast Ethernet Port:	Yes
Interfaces/Ports:	2 x RJ-45 10/100Base-TX LAN
Connectivity Media:	Twisted Pair 10/100Base-TX
Number of Expansion Slots:	11
Expansion Slots:	(2 Total /1 Free /1 Populated) AIM
Modules:	1 x PVDM2-32 Packet Voice/Fax DSP Module
Management:	Simple Network Management Protocol (SNMPv3)
Security Features:	DES
Standard Memory:	256 MB
Maximum Memory:	1 GB
Memory Technology:	DRAM
Flash Memory:	128MB
Operating System:	Cisco IOS 12.3(8)T
Input Voltage:	110 V AC
Input Voltage Range:	100 V AC to 240 V AC
Power Source:	Power Supply
Redundant Power Supply:	Yes
Compatible Rack Unit:	2U
Form Factor:	Rack-mountable
Product Code	C2811-15UC-VSEC/K9
Brand	CISCO

Replacement / Alternative Options

If the C2811-15UC-VSEC/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C2811-15UC/K9	2811 w/ PVDM2-32,AIM-CUE,15 CME/CUE/Ph lic,SP Serv,128F/512D
C2811-2SHDSL/K9	2811 2-pair G.SHDSL bundle, HWIC-2SHDSL, SP Svcs, 128F/512D

Request availability: [Ask for current stock](#) of C2811-15UC-VSEC/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).