

C2851-35UC-VSEC/K9 - Cisco 2800 Router

Model: C2851-35UC-VSEC/K9 | Brand: CISCO

Product Overview

2851 w/ PVDM2-48,NME-CUE,35 CME/CUE/Ph lic,Adv IP,128F/512D

Product page: <https://www.linknewnet.com/products/c2851-35uc-vsec-k9>

Quick Specifications

Attribute	Value
Number of Ports:	2
Fast Ethernet Port:	Yes
Interfaces/Ports:	2 x RJ-45 10/100/1000Base-T LAN
Number of Expansion Slots:	13
Expansion Slots:	(2 Total) AIM
Modules:	1 x PVDM2-32 Packet Voice/Fax DSP Module
Management:	SNMP v3
Security Features:	DES
Standard Memory:	256 MB
Maximum Memory:	1 GB
Memory Technology:	DRAM
Flash Memory:	256MB
Operating System:	Adv IP IOS
Input Voltage:	110 V AC
Input Voltage Range:	100 V AC to 240 V AC
Power Source:	Power Supply
Redundant Power Supply:	Yes
Compatible Rack Unit:	2U
Dimensions:	3.50" Height x 17.25" Width x 16.40" Depth
Weight (Approximate):	25 lb
Product Code	C2851-35UC-VSEC/K9
Brand	CISCO

Replacement / Alternative Options

If the C2851-35UC-VSEC/K9 is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C2851-35UC/K9	2851 w/ PVDM2-48,NME-CUE,35 CME/CUE/Ph lic,SP Serv,128F/512D
C2851-H-VSEC/K9	2851H.Perf.VSEC:AIM-VPN2/SSL,PVDM2,CCME/SRST,AIS,256F/512D

Request availability: [Ask for current stock](#) of C2851-35UC-VSEC/K9 or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).