

C9130AXE-E - Cisco Catalyst 9130 WiFi 6 Access Point

Model: C9130AXE-E | Brand: CISCO

Product Overview

Cisco Catalyst 9130AX Series

Product page: <https://www.linknewnet.com/products/c9130axe-e>

Quick Specifications

Attribute	Value
Software	Catalyst 9130AXE • Cisco Unified Wireless Network Software Release 8.10MR1 or later • Cisco IOS ® XE Software Release 17.1.1 s or later
Supported wireless LAN controllers	• Cisco Catalyst 9800 Series Wireless Controllers • Cisco 3504, 5520, and 8540 Wireless Controllers and Cisco Virtual Wireless Controller
Integrated antenna	• 2.4 GHz: Peak gain 4 dBi, internal antenna, omnidirectional in azimuth • 5 GHz: Peak gain 6 dBi, internal antenna, omnidirectional in azimuth
Indicators	• Status LED indicates boot loader status, association status, operating status, boot loader warnings, and boot loader errors
Dimensions (W x L x H)	• Access point (without mounting brackets): - C9130AXE: 9.17 x 9.17 x 1.58 in. (23.3 x 23.3 x 4.0 cm)
System memory	• 2048 MB DRAM • 1024 MB flash
Warranty	Limited lifetime hardware warranty
Product Code	C9130AXE-E
Brand	CISCO

Replacement / Alternative Options

If the C9130AXE-E is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C9130AXE-A	Cisco Catalyst 9130AX Series
C9130AXE-B	Cisco Catalyst 9130AX Series

Request availability: [Ask for current stock](#) of C9130AXE-E or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).