

Cisco Router ISR 900 Series C921-4P

Model: C921-4P | Brand: CISCO

Product Overview

Features a robust internal power supply, ideal for high-security Ethernet networks.

Product page: <https://www.linknewnet.com/products/c921-4p>

Quick Specifications

Attribute	Value
WAN interfaces	2 ports Gigabit Ethernet (GE)
LAN interfaces	4-port GE managed switch
Integrated USB 2.0	Yes
Number of recommended users	● 50
Default and maximum DRAM	● Default 1 GB
Default and maximum flash memory	● 2 GB on all Cisco 900 Series ISR models; not upgradable
WAN	● Refer to Table 2 for details
LAN switch	● Refer to Table 2 for details
Separate console ports	● RJ-45
USB 2.0	● One USB 2.0 Type A port
Physical dimensions	H x W x D = 1.70 x 9.0 x 9.5 in. (4.32 x 22.86 x 24.13 cm) (includes rubber feet)
Product Code	C921-4P
Brand	CISCO

Replacement / Alternative Options

If the C921-4P is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C921-4PLTEAS	Equipped with dual LTE bands, specifically designed to meet the connectivity requirements of the ASEAN region.
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of C921-4P or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).