

Cisco Router ISR 900 Series C921-4PLTEAS

Model: C921-4PLTEAS | Brand: CISCO

Product Overview

Equipped with dual LTE bands, specifically designed to meet the connectivity requirements of the ASEAN region.

Product page: <https://www.linknewnet.com/products/c921-4plteas>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	C921-4PLTEAS
Product Name	C921-4P FDD and TDD LTE, ASEAN
Frequency Band	FDD and TDD
Connectivity Technology	LTE
Ports	4 Ports
Region	ASEAN
Maximum Data Rate	150 Mbps
Storage Temperature	-40 to 85 ??C
Operating Temperature	-20 to 60 ??C
Form Factor	Desktop
Humidity	5% to 95% (non-condensing)
Input Voltage	12V DC
Power Consumption	Max 15W
SIM Slots	2
Ethernet Ports	4 x 10/100/1000 Mbps
Security Features	VPN, Firewall
Antenna	External
LED Indicators	Power, Status, Activity
Management	Web-based, CLI
Product Code	C921-4PLTEAS
Brand	CISCO

Replacement / Alternative Options

If the C921-4PLTEAS is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C921-4P	Features a robust internal power supply, ideal for high-security Ethernet networks.
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of C921-4PLTEAS or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).