

Cisco Router ISR 900 Series C926-4P

Model: C926-4P | Brand: CISCO

Product Overview

This model supports VDSL/ADSL2+ Annex B/J, making it a versatile choice for businesses with varied broadband needs.

Product page: <https://www.linknewnet.com/products/c926-4p>

Quick Specifications

Attribute	Value
WAN interfaces	1 port GE and 1 VADSL (Annex B/J)
LAN interfaces	4-port GE managed switch
Integrated USB 2.0	Yes
High availability	● Virtual Router Redundancy Protocol (VRRP) (RFC 2338) ● HSRP ● MHSRP
Metro Ethernet	● Ethernet OA&M ● Ethernet Local Management Interface (E-LMI) ● IP SLA for Ethernet
Application visibility and control	● NBAR2 ● Flexible NetFlow (FNF) ● Performance Agent
Number of recommended users	● 50
Default and maximum DRAM	● Default 1 GB
Default and maximum flash memory	● 2 GB on all Cisco 900 Series ISR models; not upgradable
WAN	● Refer to Table 2 for details
LAN switch	● Refer to Table 2 for details
Separate console ports	● RJ-45
USB 2.0	● One USB 2.0 Type A port
Physical dimensions	H x W x D = 1.10 x 10.20 x 7.00 in. (2.80 x 25.91 x 17.78 cm) (includes rubber feet)
Product Code	C926-4P
Brand	CISCO

Replacement / Alternative Options

If the C926-4P is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C926-4PLTEGB	Includes 4G LTE capabilities over ISDN, providing advanced connectivity solutions for diverse network needs.
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of C926-4P or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).