

Cisco Catalyst 9400 Series Switch C9404R-48U-BNDL-E

Model: C9404R-48U-BNDL-E | Brand: CISCO

Product Overview

Catalyst 9400 Series 4 slot, Sup, 1xC9400-LC-48U , DNA-E LIC

Product page: <https://www.linknewnet.com/products/c9404r-48u-bndl-e>

Quick Specifications

Attribute	Value
Product Code	C9404R-48U-BNDL-E
Product Description	Catalyst 9400 Series 4 slot, Sup, 1xC9400-LC-48U , DNA-E LIC
Dimensions (H x W x D)	1.73 x 17.5 x 17.7Inches
Rack Units (RU)	6RU
Total number of slots	4
Line-card slots	2
Supervisor engine slots	2 Note:Slots 2 and 3 are reserved for supervisor engines only in Cisco Catalyst C9404R; slots 1 and 4 are reserved for line cards.
Supervisor engine redundancy	Yes
Supervisor engines supported	C9400-SUP-1,C9400-SUP-1XL,C9400-SUP-1XL-Y
Maximum PoE per slot	4320W Note: Max PoE mentioned is as per the current shipping linecard, however chassis is capable ~4800W PoE per slot.
Number of power supply bays	4
AC input power	Yes
Integrated PoE	Yes
Power supplies supported	3200W AC, 2100W AC, 3200W DC
Number of fan-tray bays	1
Location of 19-inch rack-mount	Front
10/100/1000BASE-T Gigabit (RJ45) ports	96
Switched 10 Gigabit Ethernet ports	48
Switched 1 Gigabit Ethernet ports	96
802.3 BT Type 4 (90W) Ports	96
Product Code	C9404R-48U-BNDL-E
Brand	CISCO

Replacement / Alternative Options

If the C9404R-48U-BNDL-E is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C9404R	Cisco Catalyst 9400 Series 4 slot chassis
C9404R	Cisco Catalyst 9400 Series 4 slot chassis, need to be ordered with configured accessories

Request availability: [Ask for current stock](#) of C9404R-48U-BNDL-E or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).