

Cisco Switch Catalyst 9400 C9407R-96U-BNDL-E

Model: C9407R-96U-BNDL-E | Brand: CISCO

Product Overview

Catalyst 9400 Series 7 slot, Sup, 2xC9400-LC-48U , DNA-E LIC

Product page: <https://www.linknewnet.com/products/c9407r-96u-bndl-e>

Quick Specifications

Attribute	Value
Total number of slots	7
Line-card slots	5
Supervisor engine slots	2
Supervisor engine redundancy	Yes
Supervisor engines supported	C9400-SUP-1, C9400-SUP-1XL, C9400-SUP-1XL-Y
Maximum PoE per slot	2880W
Number of power supply bays	8
AC input power	Yes
Integrated PoE	Yes
Power supplies supported	3200W AC, 2100W AC
Number of fan-tray bays	1
Location of 19-inch rack-mount	Front
Dimensions (H x W x D)	17.41 x 17.30 x 16.30 in. (44.22 x 43.94 x 41.40cm)
Rack Units (RU)	10 RU
Chassis weight (with fan tray)	63.0 lb (28.58 kg)
Mounting	19-in rack compatible (19-in. rack and cable guide hardware included)
Regulatory compliance	CE Marking
Safety	● UL 60950-1 ● CAN/CSA-C222.2 No. 60950-1 ● EN 60950-1 ● IEC 60950-1 ● AS/NZS 60950.1 ● IEEE 802.3
ROHS compliance	ROHS5
Product Code	C9407R-96U-BNDL-E
Brand	CISCO

Replacement / Alternative Options

If the C9407R-96U-BNDL-E is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C9407R	Cisco Catalyst 9400 Series 7 slot chassis Spare
C9407R	Cisco Catalyst 9400 Series 7 slot chassis

Request availability: [Ask for current stock](#) of C9407R-96U-BNDL-E or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).