

Cisco Catalyst 9600 Series Switches C9606R

Model: C9606R | Brand: CISCO

Product Overview

Cisco Catalyst 9600 Series 6 Slot Chassis, need to be configured before order

Product page: <https://www.linknewnet.com/products/c9606r>

Quick Specifications

Attribute	Value
Supervisor engines supported	C9600-SUP-1
Total number of slots	6
Line-card slots	4
Supervisor engine slots	2
Number of power supply bays	4
Number of fan-tray bays	1
Rack Units (RU)	8
Power supplies supported	2000W AC, 2000W DC
Minimum number of power supplies	2(Fully loaded 9606R chassis, Minimum 3 power supplies required if input voltage is 110V)
Input voltage	AC: 90V to 264V, 47 to 63 Hz AC DC: -40V to -72V
Operating temperature	-5° to 45° C (23° to 113° F) up to 6000 feet -5° to 40° C (23° to 104° F) up to 10,000 feet
Storage temperature	-40° to 75° C (40° to 167° F)
Altitude	-60 to 3000 m (-197 to 9843 feet)
Dimensions (H x W x D)	35.43 x 44.2 x 40.9 cm 13.95 x 17.4 x 16.1 in.
Product Code	C9606R
Brand	CISCO

Replacement / Alternative Options

If the C9606R is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
C9606R-48Y24C-BN-A	Catalyst 9600 Series 6 slot bundle,with 1xSup,2xLC,DNA-A LIC
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of C9606R or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).