

Cisco ASR 1000 Series Router ASR1002-X

Model: ASR1002-X | Brand: CISCO

Product Overview

Cisco ASR1000-series router, Build-in Gigabit Ethernet port, 5G system bandwidth, 6 x SFP ports

Product page: <https://www.linknewnet.com/products/cisco-asr-1000-series-router-asr1002-x>

Quick Specifications

Attribute	Value
Product Type	Router
Default memory	4-GB DRAM shared across route processor, ESP, and SIP
EPS support	Cisco ASR 1002-X ESP with 5-Gbps (default) Upgradable through software-activated feature license to 10, 20, or 36 Gbps
EPS bandwidth	5 to 36 Gbps
External USB flash memory	1-GB USB flash-memory support
Safety Standards	UL60950-1 CSA C22.2 No. 60950-1-03 EN 60950-1 IEC 60950-1 AS/NZS 60950.1
Width	17.2 in
Height	3.5 in
Depth	18.15 in
Weight	38.25 lb (17.36 kg) (with dual AC power supply and SPA blank covers) 39.05 lb (17.72 kg) (with dual DC power supply and blank covers)
Min Temperature	32 °F
Max Temperature	104 °F
Humidity Range	10 - 85%
Product Code	ASR1002-X
Brand	CISCO

Replacement / Alternative Options

If the ASR1002-X is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
ASR1000-2T+20X1GE=	ASR1000 2-port 10GE. 20-port GE Line Card
ASR1000-6TGE=	ASR1000 6 port 10 GE Line Card

Request availability: [Ask for current stock](#) of ASR1002-X or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).