

Cisco Catalyst 4500 E-Series Switch WS-C4506-E

Model: WS-C4506-E | Brand: CISCO

Product Overview

Cisco Catalyst 4500 E-Series Switch WS-C4506-E

Product page: <https://www.linknewnet.com/products/cisco-catalyst-4500-e-series-switch-ws-c4506-e>

Quick Specifications

Attribute	Value
Total number of slots	6
Line-card slots	5
Supervisor engine slots	1
Supervisor engine redundancy	No
Supervisor engines supported	Supervisor Engines 8-E, 8L-E, 7-E, 7L-, 6-E, and 6L-E
Maximum PoE per slot	1500W
Number of power supply bays	2
AC input power	Yes
DC input power	Yes
Integrated PoE	Yes
Width	17.38 in
Height	12.50 in
Depth	17.31 in
Chassis weight (with fan tray)	40.50 lb
Min Operating Temperature	23 °F
Max Operating Temperature	104 °F
Humidity Range Operating	10 - 90%(non-condensing)
Product Code	WS-C4506-E
Brand	CISCO

Replacement / Alternative Options

If the WS-C4506-E is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
WS-C4500X-24X-ES	Catalyst 4500-X 24 Port 10G Ent. Services, Frt-to-Bk, No P/S
WS-C4500X-40X-ES	Catalyst 4500-X 40 Port 10G Ent. Services, Frt-to-Bk, No P/S

Request availability: [Ask for current stock](#) of WS-C4506-E or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).