

PA-2FE-FX - Cisco 7200 Series Port Adapter

Model: PA-2FE-FX | Brand: CISCO

Product Overview

Cisco 7200 Series 2-Port Fast Ethernet 100Base FX Port Adapter

Product page: <https://www.linknewnet.com/products/cisco-pa-2fe-fx>

Quick Specifications

Attribute	Value
Brand	Cisco
Model	PA-2FE-FX (USED)
Series	7200 Series
Port Configuration	2-Port
Ethernet Standard	100Base-FX
Connector Type	SC
Supported Protocols	IEEE 802.3u
Maximum Distance	2 km (Multi-mode Fiber)
Bandwidth	100 Mbps (Full Duplex)
Data Transfer Rate	200 Mbps (aggregate)
Compatibility	Cisco 7200 Series Routers
Power Consumption	10W typical per port
Temperature Range	0 to 40 degrees Celsius (32 to 104 degrees Fahrenheit)
Storage Temperature Range	-40 to 70 degrees Celsius (-40 to 158 degrees Fahrenheit)
Relative Humidity	5% to 95% non-condensing
EMI	FCC Class A, CE Mark
Safety Standards	UL 1950, CSA-C22.2 No.950-95, EN60950/IEC950
LED Indicators	Link, Activity
MTBF	150,000 hours
Form Factor	Plug-in module
Product Code	PA-2FE-FX
Brand	CISCO

Replacement / Alternative Options

If the PA-2FE-FX is out of stock or end-of-life, these same-brand alternatives deliver comparable capability. Contact our sales team to confirm availability.

Model	Specification
PA-2FE-TX=	Cisco 7600 2-Port Fast Ethernet 100Base TX Port Adapter
WS-X6816-10G-2T	Cisco Catalyst 6500 Series WS-X6816-10G-2T 16 Port 10 Gigabit Ethernet Fiber Module

Request availability: [Ask for current stock](#) of PA-2FE-FX or its alternatives.

Buying from LinkNewNet

Every unit is [fully tested](#) (ports verified, firmware validated) and covered by [warranty](#).